

Features

- Analog Switch Voltage: 3.3 V, 5 V, 10 V
- Low On-State Resistance:
 - Typical 50 Ω at $V_S = 9$ V
 - Typical 60 Ω at $V_S = 4.5$ V
 - Typical 300 Ω at $V_S = 3$ V
- Bandwidth: 200 MHz
- Fast Switching Times: $t_{ON} = 60$ ns, $t_{OFF} = 50$ ns
- Break-Before-Make Switching
- Operation Temperature Range: -40°C to 125°C

Applications

- Industry Control Systems
- Battery-Powered Systems
- Audio Signal Routing
- Instrumentation

Description

The TPW4066 is a four-channel single-pole single-throw (SPST) analog switch that is suitable for use in analog or digital multiplexer/demultiplexer applications. The switch features four digital select inputs (S1, S2, S3, and S4), to control four independent switches.

The device is designed on an enhanced process that provides lower power dissipation and high switching speed. The device operates equally well as either multiplexers or de-multiplexers and has an input range that extends to the supplies.

Table of Contents

Features	1
Applications	1
Description	1
Switch Selection Guide	3
Revision History	3
Pin Configuration and Functions	4
Specifications	5
Absolute Maximum Ratings ⁽¹⁾	5
ESD, Electrostatic Discharge Protection.....	5
Recommended Operating Conditions ⁽¹⁾	5
Thermal Information.....	5
Electrical Characteristics.....	7
Electrical Characteristics (Continued).....	9
Electrical Characteristics (Continued).....	11
Typical Performance Characteristics.....	13
Test Circuit and Waveforms.....	14
Application and Implementation	15
Application Information	15
Tape and Reel Information	16
Package Outline Dimensions	17
SOP14.....	17
TSSOP14.....	18
Order Information	19
IMPORTANT NOTICE AND DISCLAIMER	20

Switch Selection Guide

Product	Switch Configuration	Supply Voltage (V)	Ron (OHM)	Bandwidth (MHz)	Package
TPW4051	8:1	12	50	200	SOP16, TSSOP16, QFN16
TPW4052	(4:1) × 2	12	50	200	SOP16, TSSOP16
TPW4053	(2:1) × 3	12	50	200	SOP16, TSSOP16
TPW4054	4:1	12	50	200	MSOP10
TPW4066	(1:1) × 4	12	50	200	SOP14, TSSOP14
TPW3111	1:1	5.5	1	100	SOT353
TPW3115	1:1	5.5	5	250	SOT353, SOT23-5
TPW4157	2:1	5.5	1	100	SOT363
TPW3157A	2:1	5.5	2	100	SOT363
TPW3221	(2:1) × 2	5.5	1	100	MSOP10
TPW3223	(2:1) × 2	5.5	1	100	QFN1.4X1.8-10

Revision History

Date	Revision	Notes
2019-12-28	Rev.Pre.0	Pre-released version.
2020-03-31	Rev.A.0	Initial version.
2025-01-04	Rev.A.1	The following updates are all about the new datasheet formats or typos, and the actual product remains unchanged. Updated to a new datasheet format. Updated the Tape and Reel Information. Updated the Package Outline Dimensions.

Pin Configuration and Functions




Table 1. Pin Functions

Pin No.	Name	I/O	Description
1	A1	I/O	Channel 1 input or output.
2	B1	I/O	Channel 1 input or output.
3	B2	I/O	Channel 2 input or output.
4	A2	I/O	Channel 2 input or output.
5	S2	I	Channel 2 select input.
6	S3	I	Channel 3 select input.
7	GND		Ground.
8	A3	I/O	Channel 3 input or output.
9	B3	I/O	Channel 3 input or output.
10	B4	I/O	Channel 4 input or output.
11	A4	I/O	Channel 4 input or output.
12	S4	I	Channel 4 select input.
13	S1	I	Channel 1 select input.
14	V _{CC}		Power supply.

Table 2. Function Table

S _x	Switch Channel
L	OFF
H	ON

Specifications

Absolute Maximum Ratings ⁽¹⁾

Parameter		Min	Max	Unit
	Supply Voltage, $V_{CC} - GND$	-0.5	13	V
	Analog Switch Voltage	-0.5	$V_{CC} + 0.5$	V
	Analog Switch Current	-25	25	mA
	Analog Switch Diode Current	-20	20	mA
	Digital Input Voltage, $\bar{E}, S2, S1, S0$	GND	$V_{CC} + 0.5$	V
	Digital Input Diode Current	-20	20	mA
T_J	Maximum Junction Temperature		150	°C
T_{STG}	Storage Temperature Range	-65	150	°C
T_L	Lead Temperature (Soldering, 10 sec)		260	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

ESD, Electrostatic Discharge Protection

Symbol	Parameter	Condition	Minimum Level	Unit
HBM	Human Body Model ESD	ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	1	kV
CDM	Charged Device Model ESD	ANSI/ESDA/JEDEC JS-002 ⁽²⁾	1	kV

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

Recommended Operating Conditions ⁽¹⁾

All test conditions: over operating temperature range, unless otherwise noted.

Parameter		Min	Max	Unit
	Supply Voltage, V_{CC}	3	12	V
	Select Input Voltage	0	V_{CC}	V
	Input Transition Rise and Fall Rate		100	ns/V
	Switch I/O Port Voltage	GND	V_{CC}	V
T_A	Operating Temperature Range	-40	125	°C

(1) The select input must be held High or Low and must not float.

Thermal Information

Package Type	θ_{JA}	θ_{JC}	Unit
SOP16	100	50	°C/W

Package Type	θ_{JA}	θ_{JC}	Unit
TSSOP16	150	60	°C/W

12-V, Quad SPST Analog Switch
Electrical Characteristics

 All test conditions: single supply, $V_{CC} = 4.5\text{ V to }5.5\text{ V}$, $GND = 0\text{ V}$, unless otherwise noted.

Symbol	Parameter	Conditions	V_{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
Power Supply								
I_{CC}	Quiescent Supply Current	$V_{IN} = 0\text{ V or }V_{CC}$	5.5	4	6	8	Max	μA
Digital Input								
V_{IH}	Input Voltage High				2	2	Min	V
V_{IL}	Input Voltage Low				0.8	0.8	Max	V
I_{IN}	Control Input Leakage	$V_{IN} = 0\text{ V or }V_{CC}$	5.5	± 0.4	± 1	± 1	Max	μA
Analog Switch								
R_{ON}		$I_{OUT} = 1\text{ mA}$, $V_{IS} = GND\text{ or }V_{CC}$	4.5	60			Typ	Ω
R_{ON}		$I_{OUT} = 1\text{ mA}$, $V_{IS} = GND\text{ or }V_{CC}$	4.5	100	130	150	Max	Ω
ΔR_{ON}	On Resistance Match between Channels	$I_{OUT} = 1\text{ mA}$, $V_{IS} = 2.5\text{ V}$	4.5	20	30	35	Max	Ω
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	4.5	60	80	80	Max	Ω
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = GND$, $V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}$, $V_{OS} = GND$	5.5	± 0.4	± 1	± 1	Max	μA
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = GND$, $V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}$, $V_{OS} = GND$	5.5	± 0.4	± 2	± 2	Max	μA
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = GND\text{ or }V_{CC}$	5.5	± 0.4	± 2	± 2	Max	μA
Dynamic Characteristics								
t_{PHL} , t_{PLH}	Switch IN to OUT Time	$C_L = 50\text{ pF}$	4.5	5			Typ	ns
t_{ON}	Switch Turn-on Time	$C_L = 50\text{ pF}$	4.5	60			Max	ns
t_{OFF}	Switch Turn-off Time	$C_L = 50\text{ pF}$	4.5	50			Max	ns
	OFF-Isolation	$f = 1\text{ MHz}$, $R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	5	-70			Typ	dB
	Crosstalk in Channel	$f = 1\text{ MHz}$, $R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	5	-70			Typ	dB
	Crosstalk in Control	Between control and any switch; $R_L = 600\ \Omega$; $f = 1\text{ MHz}$; E or Sn square wave between V_{CC} and GND	5	110			Typ	mV
BW	Bandwidth	$R_L = 50\ \Omega$	5	200			Typ	MHz
THD	Total Harmonic Distortion	$R_L = 10\text{ k}\Omega$, $f = 1\text{ kHz}$	5	0.05			Typ	%

12-V, Quad SPST Analog Switch

Symbol	Parameter	Conditions	V _{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
Capacitance								
C _{IN}	Switch Input Capacitance		5	5			Typ	pF
C _{COM}	Common Output Capacitance		5	12			Typ	pF
C _{PD}	Power Dissipation Capacitance		5	50			Typ	pF

12-V, Quad SPST Analog Switch
Electrical Characteristics (Continued)

 All test conditions: single supply, $V_{CC} = 3\text{ V to }3.6\text{ V}$, $GND = 0\text{ V}$, unless otherwise noted.

Symbol	Parameter	Conditions	V_{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
Power Supply								
I_{CC}	Quiescent Supply Current	$V_{IN} = 0\text{ V or }V_{CC}$	3.6	4	6	8	Max	μA
Digital Input								
V_{IH}	Input Voltage High				2	2	Min	V
V_{IL}	Input Voltage Low				0.8	0.8	Max	V
I_{IN}	Control Input Leakage	$V_{IN} = 0\text{ V or }V_{CC}$	3.6		± 1	± 1	Max	μA
Analog Switch								
R_{ON}		$I_{OUT} = 1\text{ mA}$, $V_{IS} = GND\text{ or }V_{CC}$	3	300			Typ	Ω
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	3	100			Typ	Ω
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = GND, V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}, V_{OS} = GND$	3.6	± 0.4	± 1	± 1	Max	μA
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = GND, V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}, V_{OS} = GND$	3.6	± 0.4	± 2	± 2	Max	μA
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = GND\text{ or }V_{CC}$	3.6	± 0.4	± 2	± 2	Max	μA
Dynamic Characteristics								
t_{PHL}, t_{PLH}	Switch IN to OUT Time	$C_L = 50\text{ pF}$	3	5			Typ	ns
t_{ON}	Switch Turn-on Time	$C_L = 50\text{ pF}$	3	70			Max	ns
t_{OFF}	Switch Turn-off Time	$C_L = 50\text{ pF}$	3	60			Max	ns
	OFF-Isolation	$f = 1\text{ MHz}, R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	3.3	-70			Typ	dB
	Crosstalk	$f = 1\text{ MHz}, R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	3.3	-70			Typ	dB
	Crosstalk in Control	Between control and any switch; $R_L = 600\ \Omega$; $f = 1\text{ MHz}$; E or Sn square wave between V_{CC} and GND	3.3	110			Typ	mV
BW	Bandwidth	$R_L = 50\ \Omega$	3.3	100			Typ	MHz
THD	Total Harmonic Distortion	$R_L = 10\text{ k}\Omega, f = 1\text{ kHz}$	3.3	0.2			Typ	%
Capacitance								
C_{IN}	Switch Input Capacitance		3.3	5			Typ	pF
C_{COM}	Common Output Capacitance		3.3	12			Typ	pF

12-V, Quad SPST Analog Switch

Symbol	Parameter	Conditions	V _{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
C _{PD}	Power Dissipation Capacitance		3.3	50			Typ	pF

Electrical Characteristics (Continued)

 All test conditions: single supply, $V_{CC} = 9\text{ V to }11\text{ V}$, $GND = 0\text{ V}$, unless otherwise noted.



Symbol	Parameter	Conditions	V_{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
Power Supply								
I_{CC}	Quiescent Supply Current	$V_{IN} = 0\text{ V or }V_{CC}$	9	8	12	16	Max	μA
Digital Input								
V_{IH}	Input Voltage High				2.4	2.4	Min	V
V_{IL}	Input Voltage Low				0.8	0.8	Max	V
I_{IN}	Control Input Leakage	$V_{IN} = 0\text{ V or }V_{CC}$	11	± 0.4	± 1	± 1	Max	μA
Analog Switch								
R_{ON}		$I_{OUT} = 1\text{ mA}$, $V_{IS} = GND\text{ or }V_{CC}$	9	50			Typ	Ω
R_{ON}		$I_{OUT} = 1\text{ mA}$, $V_{IS} = GND\text{ or }V_{CC}$	9	80	95	105	Max	Ω
ΔR_{ON}	On Resistance Match between Channels	$I_{OUT} = 1\text{ mA}$, $V_{IS} = 1\text{ V}$	9	15	25	30	Max	Ω
$R_{FLAT(ON)}$	On Resistance Flatness	$I_{OUT} = 1\text{ mA}$	9	30	40	40	Max	Ω
$I_{CH(OFF)}$	Switch OFF Leakage Current on Channel	$V_{IS} = GND$, $V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}$, $V_{OS} = GND$	11	± 0.4	± 1	± 1	Max	μA
$I_{COM(OFF)}$	Switch OFF Leakage Current on Common	$V_{IS} = GND$, $V_{OS} = V_{CC}$; or $V_{IS} = V_{CC}$, $V_{OS} = GND$	11	± 0.4	± 2	± 2	Max	μA
$I_{(ON)}$	Switch ON Leakage Current	$V_{IS} = GND\text{ or }V_{CC}$	11	± 0.4	± 2	± 2	Max	μA
Dynamic Characteristics								
t_{PHL} , t_{PLH}	Switch IN to OUT Time	$C_L = 50\text{ pF}$	9	5			Typ	ns
t_{ON}	Switch Turn-on Time	$C_L = 50\text{ pF}$	9	60			Max	ns
t_{OFF}	Switch Turn-off Time	$C_L = 50\text{ pF}$	9	50			Max	ns
	OFF-Isolation	$f = 1\text{ MHz}$, $R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	10	-70			Typ	dB
	Crosstalk	$f = 1\text{ MHz}$, $R_L = 50\ \Omega$, $C_L = 10\text{ pF}$	10	-70			Typ	dB
	Crosstalk in Control	Between control and any switch; $R_L = 600\ \Omega$; $f = 1\text{ MHz}$; E or Sn square wave between V_{CC} and GND	10	220			Typ	mV
BW	Bandwidth	$R_L = 50\ \Omega$	10	200			Typ	MHz
THD	Total Harmonic Distortion	$R_L = 10\text{ k}\Omega$, $f = 1\text{ kHz}$	10	0.03			Typ	%

12-V, Quad SPST Analog Switch

Symbol	Parameter	Conditions	V _{CC} (V)	25°C	-40°C to 85°C	-40°C to 125°C	Limit	Unit
Capacitance								
C _{IN}	Switch Input Capacitance		10	5			Typ	pF
C _{COM}	Common Output Capacitance		10	12			Typ	pF
C _{PD}	Power Dissipation Capacitance		10	50			Typ	pF

Typical Performance Characteristics

All test conditions: $V_{CC} = 5\text{ V}$, unless otherwise noted.



Test Circuit and Waveforms




Figure 3. AC Test Circuit and Test Waveforms




Figure 4. Off Isolation





Figure 5. Crosstalk

Application and Implementation



Note

Information in the following application sections is not part of the 3PEAK's component specification and 3PEAK does not warrant its accuracy or completeness. 3PEAK's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

Application Information

A 0.1- μ F bypass capacitor on V_{CC} and GND is recommended to prevent power disturbance.

Tape and Reel Information




Order Number	Package	D1 (mm)	W1 (mm)	A0 (mm) ⁽¹⁾	B0 (mm) ⁽¹⁾	K0 (mm) ⁽¹⁾	P0 (mm)	W0 (mm)	Pin1 Quadrant
TPW4066-SR	SOP14	330	21.6	6.5	9.3	2.1	8	16	Q1
TPW4066-TR	TSSOP14	330	17.6	6.8	5.5	1.5	8	12	Q1


(1) The value is for reference only. Contact the 3PEAK factory for more information.

Package Outline Dimensions

SOP14



TSSOP14



Order Information

Order Number	Operating Temperature Range	Package	Marking Information	MSL	Transport Media, Quantity	Eco Plan
TPW4066-SR	-40 to 125°C	SOP14	W4066	3	Tape and Reel, 2500	Green
TPW4066-TR	-40 to 125°C	TSSOP14	W4066	3	Tape and Reel, 3000	Green

Green: 3PEAK defines "Green" to mean RoHS compatible and free of halogen substances.

IMPORTANT NOTICE AND DISCLAIMER

Copyright© 3PEAK 2012-2025. All rights reserved.

Trademarks. Any of the 思瑞浦 or 3PEAK trade names, trademarks, graphic marks, and domain names contained in this document /material are the property of 3PEAK. You may NOT reproduce, modify, publish, transmit or distribute any Trademark without the prior written consent of 3PEAK.

Performance Information. Performance tests or performance range contained in this document/material are either results of design simulation or actual tests conducted under designated testing environment. Any variation in testing environment or simulation environment, including but not limited to testing method, testing process or testing temperature, may affect actual performance of the product.

Disclaimer. 3PEAK provides technical and reliability data (including data sheets), design resources (including reference designs), application or other design recommendations, networking tools, security information and other resources "As Is". 3PEAK makes no warranty as to the absence of defects, and makes no warranties of any kind, express or implied, including without limitation, implied warranties as to merchantability, fitness for a particular purpose or non-infringement of any third-party's intellectual property rights. Unless otherwise specified in writing, products supplied by 3PEAK are not designed to be used in any life-threatening scenarios, including critical medical applications, automotive safety-critical systems, aviation, aerospace, or any situations where failure could result in bodily harm, loss of life, or significant property damage. 3PEAK disclaims all liability for any such unauthorized use.