

# Synchronous Buck MOSFET Driver

## NCP81158D

The NCP81158D is a high-performance dual MOSFET gate driver in a small 3 mm x 3 mm package, optimized to drive the gates of both high-side and low-side power MOSFETs in a synchronous buck converter. The driver outputs can be placed into a high-impedance state via the tri-state PWM and EN inputs. The NCP81158D comes packaged with an integrated boost diode to minimize external components. A VCC UVLO function guarantees the outputs are low when the supply voltage is low.

### Features

- When Device is Powered, Fast PWM Response to EN Going High
- Space-efficient 3 mm x 3 mm DFN8 Thermally-Enhanced Package
- VCC Range of 4.5 V to 5.5 V
- Internal Bootstrap Diode
- 5 V 3-stage PWM Input
- Diode Braking Capability via EN Mid-state
- Adaptive Anti-cross Conduction Circuit Protects Against Cross-conduction during FET Turn-on and Turn-off
- Output Disable Control Turns Off Both MOSFETs via Enable Pin
- VCC Undervoltage Lockout
- These Devices are Pb-free, Halogen-free/BFR-free and are RoHS Compliant


### Typical Applications

- Power Solutions for Notebook and Desktop Systems



DFN8  
CASE 506BJ

### MARKING DIAGRAM



1158D = Specific Device Code

A = Assembly Location

L = Wafer Lot


Y = Year

W = Work Week

▪ = Pb-free Package

(Note: Microdot may be in either location)

### PINOUT DIAGRAM



### ORDERING INFORMATION

| Device         | Package           | Shipping†             |
|----------------|-------------------|-----------------------|
| NCP81158DMNTXG | DFN8<br>(Pb-free) | 3000 / Tape &<br>Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# NCP81158D




Figure 1. Block Diagram

## PIN DESCRIPTIONS

| Pin No. | Symbol | Description                                                                                                                                                                                                                                                                  |
|---------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1       | BST    | Floating bootstrap supply pin for high side gate driver. Connect the bootstrap capacitor between this pin and the SW pin.                                                                                                                                                    |
| 2       | PWM    | Control input. The PWM signal has three distinctive states: Low = Low Side FET Enabled, Mid = Diode Emulation Enabled, High = High Side FET Enabled.                                                                                                                         |
| 3       | EN     | Logic input. A logic high to enable the part and a logic low to disable the part. Three states logic input:<br>EN = High to enable the gate driver;<br>EN = Low to disable the driver;<br>EN = Mid to go into diode mode (both high and low side gate drive signals are low) |
| 4       | VCC    | Power supply input. Connect a bypass capacitor (0.1 $\mu$ F) from this pin to ground.                                                                                                                                                                                        |
| 5       | DRVL   | Low side gate drive output. Connect to the gate of low side MOSFET.                                                                                                                                                                                                          |
| 6       | GND    | Bias and reference ground. All signals are referenced to this node.                                                                                                                                                                                                          |
| 7       | SW     | Switch node. Connect this pin to the source of the high side MOSFET and drain of the low side MOSFET.                                                                                                                                                                        |
| 8       | DRVH   | High side gate drive output. Connect to the gate of high side MOSFET.                                                                                                                                                                                                        |
| 9       | FLAG   | Thermal flag. There is no electrical connection to the IC. Connect to ground plane.                                                                                                                                                                                          |

# NCP81158D

## APPLICATION CIRCUIT




Figure 2. Application Circuit

**DISCONTINUED**  
THIS DEVICE IS NOT RECOMMENDED FOR NEW DESIGN  
PLEASE CONTACT YOUR onsemi  
REPRESENTATIVE FOR INFORMATION

# NCP81158D

## ABSOLUTE MAXIMUM RATINGS

### ELECTRICAL INFORMATION

| Symbol          | Pin Name                                 | V <sub>MAX</sub>                                                                 | V <sub>MIN</sub>                        |
|-----------------|------------------------------------------|----------------------------------------------------------------------------------|-----------------------------------------|
| V <sub>CC</sub> | Main Supply Voltage Input                | 6.5 V<br>7.5 V < 80 ns                                                           | -0.3 V                                  |
| BST             | Bootstrap Supply Voltage                 | 35 V wrt/ GND<br>40 V ≤ 50 ns wrt/ GND<br>6.5 V wrt/ SW<br>7.7 V < 50 ns wrt/ SW | -0.3 V wrt/SW                           |
| SW              | Switching Node (Bootstrap Supply Return) | 35 V<br>40 V ≤ 80 ns                                                             | -5 V<br>-10 V (200 ns)                  |
| DRVH            | High Side Driver Output                  | BST + 0.3 V<br>SW + 7 V (< 80 ns)                                                | -0.3 V wrt/SW<br>-2 V (< 200 ns) wrt/SW |
| DRVL            | Low Side Driver Output                   | V <sub>CC</sub> + 0.3 V<br>7 V (< 80 ns)                                         | -0.3 V DC<br>-5 V (< 200 ns)            |
| PWM             | DRVH and DRVL Control Input              | 6.5 V                                                                            | -0.3 V                                  |
| EN              | Enable Pin                               | 6.5 V                                                                            | -0.3 V                                  |
| GND             | Ground                                   | 0 V                                                                              | 0 V                                     |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

\*All signals referenced to AGND unless noted otherwise.

### THERMAL INFORMATION

| Symbol           | Parameter                                     | Value       | Unit |
|------------------|-----------------------------------------------|-------------|------|
| R <sub>θJA</sub> | Thermal Characteristic QFN Package (Note 1)   | 119         | °C/W |
| T <sub>J</sub>   | Operating Junction Temperature Range (Note 2) | -40 to 150  | °C   |
| T <sub>A</sub>   | Operating Ambient Temperature Range           | -40 to +100 | °C   |
| T <sub>STG</sub> | Maximum Storage Temperature Range             | -55 to +150 | °C   |
| MSL              | Moisture Sensitivity Level – QFN Package      | 1           |      |

\*The maximum package power dissipation must be observed.

1. 1 in<sup>2</sup> Cu, 1 oz. thickness.

2. JESD 51-7 (1S2P Direct-Attach Method) with 1 LFM.

**NCP81158D ELECTRICAL CHARACTERISTICS** (-40°C < T<sub>A</sub> < +100°C; 4.5 V < V<sub>CC</sub> < 5.5 V, 4.5 V < BST-SWN < 5.5 V, 4.5 V < BST < 30 V, 0 V < SWN < 21 V, unless otherwise noted)

| Parameter | Test Conditions | Min | Typ | Max | Unit |
|-----------|-----------------|-----|-----|-----|------|
|-----------|-----------------|-----|-----|-----|------|

#### SUPPLY VOLTAGE

|                                   |  |     |  |     |   |
|-----------------------------------|--|-----|--|-----|---|
| V <sub>CC</sub> Operation Voltage |  | 4.5 |  | 5.5 | V |
|-----------------------------------|--|-----|--|-----|---|

#### UNDERVOLTAGE LOCKOUT

|                                 |  |     |      |     |    |
|---------------------------------|--|-----|------|-----|----|
| V <sub>CC</sub> Start Threshold |  | 3.8 | 4.35 | 4.5 | V  |
| V <sub>CC</sub> UVLO Hysteresis |  | 150 | 200  | 250 | mV |

#### SUPPLY CURRENT

|                 |                                                                                          |  |     |     |    |
|-----------------|------------------------------------------------------------------------------------------|--|-----|-----|----|
| Shutdown Mode   | I <sub>CC</sub> + I <sub>BST</sub> , EN = GND                                            |  | 690 | 900 | μA |
| Normal Mode     | I <sub>CC</sub> + I <sub>BST</sub> , EN = 5 V, PWM = OSC                                 |  | 4.7 |     | mA |
| Standby Current | I <sub>CC</sub> + I <sub>BST</sub> , EN = HIGH, PWM = LOW,<br>No loading on DRVH & DRVL  |  | 0.9 |     | mA |
| Standby Current | I <sub>CC</sub> + I <sub>BST</sub> , EN = HIGH, PWM = HIGH,<br>No loading on DRVH & DRVL |  | 1.1 |     | mA |

#### BOOTSTRAP DIODE

|                 |                                                    |     |     |     |   |
|-----------------|----------------------------------------------------|-----|-----|-----|---|
| Forward Voltage | V <sub>CC</sub> = 5 V, forward bias current = 2 mA | 0.1 | 0.4 | 0.6 | V |
|-----------------|----------------------------------------------------|-----|-----|-----|---|

# NCP81158D

**NCP81158D ELECTRICAL CHARACTERISTICS** ( $-40^{\circ}\text{C} < T_A < +100^{\circ}\text{C}$ ;  $4.5\text{ V} < V_{CC} < 5.5\text{ V}$ ,  $4.5\text{ V} < \text{BST-SWN} < 5.5\text{ V}$ ,  $4.5\text{ V} < \text{BST} < 30\text{ V}$ ,  $0\text{ V} < \text{SWN} < 21\text{ V}$ , unless otherwise noted)

| Parameter                                                   | Test Conditions                                                                  | Min  | Typ  | Max | Unit          |
|-------------------------------------------------------------|----------------------------------------------------------------------------------|------|------|-----|---------------|
| <b>PWM INPUT</b>                                            |                                                                                  |      |      |     |               |
| PWM Input High                                              |                                                                                  | 3.4  |      |     | V             |
| PWM Mid-State                                               |                                                                                  | 1.3  |      | 2.7 | V             |
| PWM Input Low                                               |                                                                                  |      |      | 0.7 | V             |
| ZCD Blanking Timer                                          |                                                                                  |      | 350  |     | ns            |
| <b>HIGH SIDE DRIVER</b>                                     |                                                                                  |      |      |     |               |
| Output Impedance, Sourcing Current                          | $V_{\text{BST}} - V_{\text{SW}} = 5\text{ V}$                                    |      | 0.9  | 1.7 | $\Omega$      |
| Output Impedance, Sinking Current                           | $V_{\text{BST}} - V_{\text{SW}} = 5\text{ V}$                                    |      | 0.7  | 1.7 | $\Omega$      |
| DRVH Rise Time $t_{\text{rDRVH}}$                           | $V_{CC} = 5\text{ V}$ , 3 nF load, $V_{\text{BST}} - V_{\text{SW}} = 5\text{ V}$ |      | 16   | 25  | ns            |
| DRVH Fall Time $t_{\text{fDRVH}}$                           | $V_{CC} = 5\text{ V}$ , 3 nF load, $V_{\text{BST}} - V_{\text{SW}} = 5\text{ V}$ |      | 11   | 18  | ns            |
| DRVH Turn-Off Propagation Delay $t_{\text{pd}1\text{DRVH}}$ | $C_{\text{LOAD}} = 3\text{ nF}$                                                  | 10   |      | 30  | ns            |
| DRVH Turn-On Propagation Delay $t_{\text{pd}h\text{DRVH}}$  | $C_{\text{LOAD}} = 3\text{ nF}$                                                  | 10   |      | 40  | ns            |
| SW Pulldown Resistance                                      | SW to PGND                                                                       |      | 45   |     | k $\Omega$    |
| DRVH Pulldown Resistance                                    | DRVH to SW, $\text{BST-SW} = 0\text{ V}$                                         |      | 45   |     | k $\Omega$    |
| <b>LOW SIDE DRIVER</b>                                      |                                                                                  |      |      |     |               |
| Output Impedance, Sourcing Current                          |                                                                                  |      | 0.9  | 1.7 | $\Omega$      |
| Output Impedance, Sinking Current                           |                                                                                  |      | 0.4  | 0.8 | $\Omega$      |
| DRVL Rise Time $t_{\text{rDRVL}}$                           | $C_{\text{LOAD}} = 3\text{ nF}$                                                  |      | 16   | 25  | ns            |
| DRVL Fall Time $t_{\text{fDRVL}}$                           | $C_{\text{LOAD}} = 3\text{ nF}$                                                  |      | 11   | 15  | ns            |
| DRVL Turn-Off Propagation Delay $t_{\text{pd}1\text{DRVL}}$ | $C_{\text{LOAD}} = 3\text{ nF}$                                                  | 10   |      | 30  | ns            |
| DRVL Turn-On Propagation Delay $t_{\text{pd}h\text{DRVL}}$  | $C_{\text{LOAD}} = 3\text{ nF}$                                                  | 5.0  |      | 25  | ns            |
| DRVL Pulldown Resistance                                    | DRVL to PGND, $V_{CC} = \text{PGND}$                                             |      | 45   |     | k $\Omega$    |
| <b>EN INPUT</b>                                             |                                                                                  |      |      |     |               |
| Input Voltage High                                          |                                                                                  | 3.3  |      |     | V             |
| Input Voltage Mid                                           |                                                                                  | 1.35 |      | 1.8 | V             |
| Input Voltage Low                                           |                                                                                  |      |      | 0.6 | V             |
| Input bias current                                          |                                                                                  | -1.0 |      | 1.0 | $\mu\text{A}$ |
| Propagation Delay Time, Falling                             | EN falling past 0.6V to DRVL @ 90%, PWM = 0V                                     |      | 20   | 40  | ns            |
| Propagation Delay Time, Rising                              | EN rising past 3.3V to DRVL @ 10%, PWM = 0V                                      |      | 25   |     | ns            |
| <b>SW NODE</b>                                              |                                                                                  |      |      |     |               |
| SW Node Leakage Current                                     |                                                                                  |      |      | 20  | $\mu\text{A}$ |
| Zero Cross Detection Threshold Voltage                      |                                                                                  |      | -6.0 |     | mV            |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

**Table 1. DECODER TRUTH TABLE**

| Input                  | ZCD                                   | DRVL | DRVH |
|------------------------|---------------------------------------|------|------|
| PWM High (Enable High) | ZCD Reset                             | Low  | High |
| PWM Mid (Enable High)  | Positive Current Through the Inductor | High | Low  |
| PWM Mid (Enable High)  | Zero Current Through the Inductor     | Low  | Low  |
| PWM Low (Enable High)  | ZCD Reset                             | High | Low  |
| Enable at Mid          | X                                     | Low  | Low  |




Figure 3. Gate Timing Diagram




Figure 4. Timing Diagram

## APPLICATION INFORMATION

The NCP81158D gate driver is a single-phase MOSFET driver designed for driving N-channel MOSFETs in a synchronous buck converter topology.

### Low-Side Driver

The low-side driver is designed to drive a ground-referenced low- $R_{DS(on)}$  N-channel MOSFET. The voltage supply for the low-side driver is internally connected to the VCC and GND pins.

### High-Side Driver

The high-side driver is designed to drive a floating low- $R_{DS(on)}$  N-channel MOSFET. The gate voltage for the high-side driver is developed by a bootstrap circuit referenced to the SW pin.

The bootstrap circuit is comprised of the integrated diode and an external bootstrap capacitor. When the NCP81158D is starting up, the SW pin is held at ground, allowing the

bootstrap capacitor to charge up to VCC through the bootstrap diode. When the PWM input is driven high, the high-side driver will turn on the high-side MOSFET using the stored charge of the bootstrap capacitor. As the high-side MOSFET turns on, the SW pin rises. When the high-side MOSFET is fully turned on, SW will settle to VIN and BST will settle to VIN + VCC (excluding parasitic ringing).

### Bootstrap Circuit

The bootstrap circuit relies on an external charge storage capacitor (C<sub>BST</sub>) and an integrated diode to provide current to the high-side driver. A multi-layer ceramic capacitor (MLCC) with a value greater than 100 nF should be used for C<sub>BST</sub>.

### Power Supply Decoupling

The NCP81158D can source and sink relatively large currents to the gate pins of the MOSFETs. In order to maintain a constant and stable supply voltage, a low-ESR capacitor should be placed near the VCC and GND pins. A MLCC between 1 µF and 4.7 µF is typically used.

### Undervoltage Lockout

DRVH and DRVL are low until VCC reaches the VCC UVLO threshold, typically 4.35 V. Once VCC reaches this threshold, the PWM signal will control DRVH and DRVL. There is a 200 mV hysteresis on VCC UVLO. There are pull-down resistors on DRVH, DRVL and SW to prevent the gates of the MOSFETs from accumulating enough charge to turn on when the driver is powered off.

Whenever VCC rises above the VCC UVLO threshold, an auto-calibration cycle of the ZCD threshold is conducted. DRVH and DRVL outputs will be pulled low during this auto-calibration cycle, thus not responding to the PWM input. The auto-calibration cycle takes 30 µs, typically.

### Three-State EN Input

Placing EN into a logic-high and logic-low will turn the driver on and off, respectively, as long as VCC is greater than the UVLO threshold. The EN threshold limits are specified in the electrical characteristics table in this datasheet. Setting the voltage on EN to a mid-state level will pull both DRVH and DRVL low.

Setting EN to the mid-state level can be used for body diode braking to quickly reduce the inductor current. By turning the LS FET off and having the current conduct through the LS FET body diode, the voltage at the switch node will be at a greater negative potential compared to having the LS FET on. This greater negative potential on switch node allows there to be a greater voltage across the output inductor, since the opposite terminal of the inductor is connected to the converter output voltage. The larger voltage across the inductor causes there to be a greater inductor current slew rate, allowing the current to decrease at a faster rate.

### Three-State PWM Input

Switching PWM between logic-high and logic-low states will allow the driver to operate in continuous conduction mode as long as VCC is greater than the UVLO threshold and EN is high. The threshold limits are specified in the electrical characteristics table in this datasheet. Refer to Figure 21 for the gate timing diagrams and Table 1 for the EN/PWM logic table.

When PWM is set above PWM<sub>HI</sub>, DRVL will first turn off after a propagation delay of t<sub>pdL</sub>DRVL. To ensure non-overlap between DRVL and DRVH, there is a delay of t<sub>pdh</sub>DRVH from the time DRVL falls to 1 V, before DRVH is allowed to turn on.

When PWM falls below PWM<sub>LO</sub>, DRVH will first turn off after a propagation delay of t<sub>pdL</sub>DRVH. To ensure non-overlap between DRVH and DRVL, there is a delay of t<sub>pdh</sub>DRVL from the time DRVH – SW falls to 1 V, before DRVL is allowed to turn on.

When PWM enters the mid-state voltage range, DRVL goes high after the non-overlap delay, and stays high for the duration of the ZCD blanking + debounce timers. Once these timers expire, SW is monitored for zero current detection and pulls DRVL low once zero current is detected.

### Thermal Considerations

As power in the NCP81158D increases, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and the ambient temperature affect the rate of junction temperature rise for the part. When the NCP81158D has good thermal conductivity through the PCB, the junction temperature will be relatively low with high power applications. The maximum dissipation the NCP81158D can handle is given by:

$$P_{D(MAX)} = \frac{[T_{J(MAX)} - T_A]}{R_{\theta JA}} \quad (\text{eq. 1})$$

Since T<sub>J</sub> is not recommended to exceed 150°C, the NCP81158D, soldered on to a 645 mm<sup>2</sup> copper area, using 1 oz. copper and FR4, can dissipate up to 1.05 W when the ambient temperature (T<sub>A</sub>) is 25°C. The power dissipated by the NCP81158D can be calculated from the following equation:

$$P_D \approx VCC \cdot [(n_{HS} \cdot Q_{gHS} + n_{LS} \cdot Q_{gLS}) \cdot f + I_{standby}] \quad (\text{eq. 2})$$








Where n<sub>HS</sub> and n<sub>LS</sub> are the number of high-side and low-side FETs, respectively, Q<sub>gHS</sub> and Q<sub>gLS</sub> are the gate charges of the high-side and low-side FETs, respectively and f is the switching frequency of the converter.



SCALE 2:1

**DFN8 3x3, 0.5P**  
**CASE 506BJ**  
**ISSUE O**

DATE 08 NOV 2007



**DETAIL A**  
**OPTIONAL**  
**CONSTRUCTION**

**DETAIL A**  
**OPTIONAL**  
**CONSTRUCTION**

**DETAIL B**  
**OPTIONAL**  
**CONSTRUCTION**
**SOLDERMASK DEFINED**  
**MOUNTING FOOTPRINT**


DIMENSION: MILLIMETERS

**NOTES:**

1. DIMENSIONS AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| MILLIMETERS |      |      |
|-------------|------|------|
| DIM         | MIN  | MAX  |
| A           | 0.80 | 1.00 |
| A1          | 0.00 | 0.05 |
| A3          | 0.20 | REF  |
| b           | 0.18 | 0.30 |
| D           | 3.00 | BSC  |
| D2          | 1.64 | 1.84 |
| E           | 3.00 | BSC  |
| E2          | 1.35 | 1.55 |
| e           | 0.50 | BSC  |
| K           | 0.20 | ---  |
| L           | 0.30 | 0.50 |
| L1          | 0.00 | 0.03 |

**GENERIC**  
**MARKING DIAGRAM\***


- XXXXX = Specific Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking.

Pb-Free indicator, "G" or microdot "▪", may or may not be present.

\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

|                         |                       |                                                                                                                                                                                     |
|-------------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON25786D</b>    | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>DFN8 3X3, 0.5P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)