


6 A, 33 mΩ, 2.8 V to 22 V eFuse With Accurate Current Limit and Programmable OVP



DESCRIPTION

The SIPQ32434A and SIPQ32434B are single channel eFuses protect both power sources and downstream circuitry from excessive inrush currents, overloads, short circuits, and over voltage faults. They provide increased controllability and reliability with simplified designs with minimal external components.

V_{IN} overvoltage protection and undervoltage lockout threshold levels can be set with an external resistor network. V_{IN} inrush current can be set with a soft start capacitor. The output current limit can be set by a resistor connected to I_{LIM} pin. I_{LIM} pin voltage can also serve as switch current reporting.

Upon switch-off due to latchable faults, the SIPQ32434A will latch the power switch off and the PGD will remain low. The switch can restart by resetting the EN or V_{IN} . The SIPQ32434B will auto retry if there is no OTP or OVP fault. The retry delay time is 32 times the soft start time set by the C_{SS} .

The switch is characterized for operation over a junction temperature range of -40°C to $+125^{\circ}\text{C}$.

FEATURES

- Qualified for automotive applications
- AEC-Q100 qualified:
 - Device temperature grade 1
 - Device HBM ESD classification level 2
 - Device CDM ESD classification level C4B method 2
- 2.8 V to 22 V operation voltage
- 28 V max. DC tolerance on V_{IN}
- 33 mΩ typical switch resistance
- 0.5 A to 6 A current limit setting range
- Current limit accuracy of $\pm 7\%$
- Fast short circuit protection response
- OCP triggering without overhead current
- Programmable turn-on slew rate
- Adjustable OVP (and fixed 24 V OVP at V_{IN})
- Adjustable UVLO
- Over-temperature protection
- PGD: power good indicator output
- Compact TDFN10 3 mm x 3 mm package wettable flank
- Active reverse blocking feature available with SIPQ32433
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE
GRADE

RoHS
COMPLIANT
HALOGEN
FREE

APPLICATIONS

- Automotive infotainment
- ADAS and auto-pilot
- Cameras and sensors
- USB hubs
- Holdup power switching
- Power management

TYPICAL APPLICATION CIRCUIT




Fig. 1 - Application Circuit

**ORDERING INFORMATION**

PART NUMBER	OCF RESPONSE	$R_{DS(on)}$ (m Ω)	TRUE REVERSE CURRENT BLOCKING	REPORT	MARKING CODE	PACKAGE	LEAD FINISH
SIPQ32434ADN-T1E3	Latch	33	No	PG	Q434A	DFN10 3 mm x 3 mm	Matte tin
SIPQ32434BDN-T1E3	Auto-retry	33	No	PG	Q434B	DFN10 3 mm x 3 mm	
SIPQ32434AEVB	Evaluation board						Evaluation board
SIPQ32434BEVB							

ABSOLUTE MAXIMUM RATINGS

PARAMETER	CONDITION	LIMIT	UNIT
Input voltage (V_{IN})	Reference to GND	-0.3 to +28	V
Output voltage (V_{OUT})	Reference to GND	-0.3 to ($V_{IN} + 0.3$) or 28, whichever comes first	
		-5 V for +5 μ s	
EN voltage	Reference to GND	-0.3 to +28	
OVP	Reference to GND	-0.3 to +6.0	
SS	Reference to GND	-0.3 to +6.0	
I_{LIM}		-0.3 to +6.0	
PGD		-0.3 to +6.0	
Maximum continuous switch current	SIPQ32434	6	A
Thermal resistance (θ_{JA})		44.8	$^{\circ}$ C/W
ESD rating	HBM	± 2	kV
ESD rating	CDM	± 0.75	
Latch up current (V_{IN} and V_{OUT})	Per JESD78E	200	mA
MSL rating		MSL1	
Temperature			
Operating junction temperature		-40 to 150	$^{\circ}$ C
Storage temperature		-65 to +150	

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

RECOMMENDED OPERATING RANGE


ELECTRICAL	LIMIT	UNIT
Input voltage (V_{IN})	3 to 22	V
Operating junction temperature	-40 to +125	$^{\circ}$ C

**ELECTRICAL SPECIFICATIONS**

PARAMETER	SYMBOL	TEST CONDITIONS UNLESS SPECIFIED $V_{IN} = 12\text{ V}$, $T_J = -40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$, $V_{EN(H)} = 2.4\text{ V}$, $C_{OUT} = 0.1\text{ }\mu\text{F}$, $R_{LIM} = 4.1\text{ k}\Omega$	LIMITS			UNIT
			MIN.	TYP.	MAX.	
Power Supply						
V_{IN} max. DC tolerance	$V_{IN(max.)}$		-	-	28	V
V_{IN} operation voltage	V_{IN}	Operating input voltage range	2.8	-	22	
Quiescent current	$I_{Q(ON)}$	$EN = 1.8\text{ V}$, $V_{IN} = 2.8\text{ V}$ to 28 V , V_{OUT} open	-	230	340	μA
Shutdown current	$I_{Q(SD)}$	$V_{IN} = 2.8\text{ V}$ to 28 V , $EN = 0\text{ V}$, $T_A = 25\text{ }^{\circ}\text{C}$	-	0.8	5	
OVP switch-off current	$I_{Q(OVP)}$	$V_{IN} = 2.8\text{ V}$ to 28 V , $EN = 2.4\text{ V}$, $OVP = 1.4\text{ V}$	-	1	-	
VIN ULVO						
Switch V_{OUT} leakage	I_{UVLO_OUT}	$V_{IN} = 2.3\text{ V}$	-500	-	+500	nA
Switch V_{IN} leakage	I_{UVLO_IN}		-	27	50	μA
Overvoltage Protection						
OVP threshold	V_{OVP}	$V_{IN} = 12\text{ V}$, OVP rising, $T_A = 25\text{ }^{\circ}\text{C}$	1.14	1.2	1.26	V
OVP hysteresis	OVP_{HST}		45	105	140	mV
OVP leakage	I_{OVP}	$V_{OVP} = 1.2\text{ V}$ on the pin, $T_A = 25\text{ }^{\circ}\text{C}$	-	40	100	nA
V_{IN} pin internal fixed OVP	IN_{OVP}	$T_A = 25\text{ }^{\circ}\text{C}$	23	24	25.6	V
EN / UVLO						
EN on threshold	V_{UVPR}	V_{EN} rising	-	1.25	-	V
EN off threshold	V_{UVPF}	V_{EN} falling	-	1.05	-	
EN / UVLO leakage		$V_{EN} = 1.2\text{ V}$	-0.25	-	+0.25	μA
Soft start bias current	I_{SS}		-	5	-	μA
Overcurrent Protection						
Current limit voltage threshold	V_{OCP}	Voltage that triggers the OCP shown on I_{LIM} pin	-	0.6	-	VCu
Current limit accuracy	I_{OCP}	$V_{IN} - V_{OUT} = 1\text{ V}$, $R_{LIM} = 2.06\text{ k}\Omega$	5.58	6	6.42	A
		$V_{IN} - V_{OUT} = 1\text{ V}$, $R_{LIM} = 3.53\text{ k}\Omega$	3.22	3.5	3.78	
		$V_{IN} - V_{OUT} = 1\text{ V}$, $R_{LIM} = 8.24\text{ k}\Omega$	1.32	1.5	1.68	
		$V_{IN} - V_{OUT} = 1\text{ V}$, $R_{LIM} = 24.72\text{ k}\Omega$	0.43	0.5	0.58	
Current limit setting range		Minimum $R_{LIM} = 1.74\text{ k}\Omega$	0.5	-	7.1	
Current limit hold-up time	t_{LIM}	Current limiting timeout, if no OTP	3	6	9	ms
Power Switch						
ON resistance	$R_{DS(ON)}$	$V_{IN} = 5\text{ V}$ to 22 V , $I_{OUT} = 1\text{ A}$, $T_J = 25\text{ }^{\circ}\text{C}$	-	33	41	m Ω
		$V_{IN} = 5\text{ V}$ to 22 V , $I_{OUT} = 1\text{ A}$, $T_J = 85\text{ }^{\circ}\text{C}$	-	-	48	
PGD, Power Good						
PGD pull-down resistance	R_{PG}	$V_{IN} = 5\text{ V}$, output pin = 0.1 V	-	5.2	10	Ω
PGD oll leakage	I_{PG}	Biased with 5 V_{DC}	-	0.01	1	μA



SWITCHING CHARACTERISTICS						
PARAMETER	SYMBOL	TEST CONDITIONS UNLESS SPECIFIED V _{IN} = 12 V, T _J = -40 °C to +125 °C, V _{EN(H)} = 2.4 V, C _{OUT} = 0.1 μF, R _{LIM} = 4.1 kΩ	LIMITS			UNIT
			MIN.	TYP.	MAX.	
EN / UVLO						
Switch turn-on delay time	T _{ON_DLY}	From EN / UVLO voltage, V _{UVPR} to V _{OUT} reaches 10 % V _{IN} , R _L = 10 Ω, C _L = 10 μF, C _{SS} open	-	220	-	μs
Shutdown delay	T _{OFF_DLY}	From EN / UVLO low to V _{OUT} = 0.9 x V _{IN} , R _L = 10 Ω, C _L = 10 μF, C _{SS} open	-	10	-	
OVP Timing						
OVP off time	t _{OVP}	R _L = 100 Ω, C _L = 0 μF, OVP steps from 1 V to 1.4 V; measured from OVP pin voltage crossing 1.2 V threshold to V _{OUT} = 0.9 x V _{IN}	-	0.3	1	μs
Internal OVP off time	t _{OVP_INT}	R _L = 100 Ω, C _L = 0 μF, V _{IN} steps from 22 V to 26 V; measured from V _{IN} pin voltage crossing 24 V threshold to V _{OUT} = 0.9 x V _{IN}	-	1.5	-	
Flag reporting delay		PGD pull up to 5 V through a 100 kΩ; delay time from OVP pin voltage step to PGD is below 0.5 V	-	-	2	
Overcurrent protection						
Moderate overcurrent protection	t _{OCP}	Load current is 120 % of current limit threshold	-	1.1	-	μs
Soft Start Control						
Output rise up time	t _R	V _{IN} = 12 V, R _L = 10 Ω, C _L = 10 μF, V _{OUT} from 10 % to 90 % V _{IN} , C _{SS} open	-	560	-	μs
		V _{IN} = 12 V, R _L = 10 Ω, C _L = 10 μF, V _{OUT} from 10 % to 90 % V _{IN} , C _{SS} = 22 nF	-	4.7	-	ms
SS charge current			-	5	-	μA
Auto Retry						
Auto retry cycle	RTY _{cnt}	Delay time of restart after all faults are removed; this is defined as the number of cycles of soft start time set by C _{SS}	-	32	-	
Thermal Shutdown						
Thermal shutdown		Temperature increases	-	165	-	°C
Thermal shutdown hysteresis			-	45	-	°C

PACKAGE OUTLINE



DFN10, pin 1 dot marking is on top of the device







Fig. 2 - Pin Out Drawing (top view)







PIN DESCRIPTION		
PIN #	NAME	FUNCTION
1, 2	V_{IN}	Power switch input pins; two pins are fused inside the package
3	SS	A capacitor from this pin to GND sets output voltage slew rate
4	EN / UVLO	Active gigh switch control input; $V_{THL} < 0.3 V$, $V_{THH} > 1.4 V$
5	I_{LIM} / I_{MON}	A resistor from this pin to GND sets the overload and short-circuit current limit; the pin can be used for current reporting, referring to the voltage developed over the current limit setting resistor
6	GND	Ground
7	OVP	Input for setting the programmable overvoltage protection threshold. An overvoltage event turns-off the internal FET and asserts FLT to indicate the overvoltage fault
8	PGD	Open drain output, when V_{OUT} is $\geq 95 \% V_{IN}$, and none of the following faults are triggered: OT, OC, OV
9, 10	V_{OUT}	Power switch output pins; two pins are fused inside the package
Exposed pad	GND	The package's central exposed pad must be connected to the ground plane; optimal PCB thermal design will enhance device performance






FUNCTIONAL BLOCK DIAGRAM AND TRUTH TABLE

TRUTH TABLE	
EN	SWITCH
1	ON
0	OFF


Fig. 3 - Device Block Diagram


Fig. 4 - Quiescent Current vs. Input

Fig. 7 - Switch Off Current vs. Input

Fig. 5 - Quiescent Current vs. Temperature

Fig. 8 - On Resistance vs. Input

Fig. 6 - Shutdown Current vs. Input

Fig. 9 - Shutdown Current vs. Temperature


Fig. 10 - Switch Off Current vs. Temperature

Fig. 13 - Threshold Voltage vs. Input Voltage V_{IN}

Fig. 11 - On Resistance vs. Temperature

Fig. 14 - Soft Start Current vs. Temperature

Fig. 12 - Soft Start Current vs. Input Voltage V_{IN}

Fig. 15 - EN Current vs. EN Voltage


Fig. 16 - Enable Resistance vs. Temperature

Fig. 19 - Turn Off Delay Time vs. Temperature

Fig. 17 - Rise Time vs. Temperature

Fig. 20 - Overvoltage Protection Threshold vs. Temperature

Fig. 18 - Turn On Delay Time vs. Temperature



TYPICAL CHARACTERISTICS




Fig. 21 - Turn On by EN
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_L = 220\ \mu\text{F}$, $C_{SS} = 22\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 24 - Turn On by Hot-Plug of V_{IN}
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_L = 220\ \mu\text{F}$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$
EN Voltage Divider Resistors, $1\text{ M}\Omega$ and $127\text{ k}\Omega$




Fig. 22 - Turn Off by EN
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_L = 220\ \mu\text{F}$, $C_{SS} = 22\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 25 - Turn On by V_{IN} When EN is 3 V
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_L = 220\ \mu\text{F}$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 23 - Turn On by V_{IN}
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_L = 220\ \mu\text{F}$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$
EN Voltage Divider Resistors, $1\text{ M}\Omega$ and $127\text{ k}\Omega$




Fig. 26 - Turn On by EN Into Resistive Load
 $V_{IN} = 12\text{ V}$, $R_L = 6\ \Omega$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 27 - Turn On by EN Into Capacitive Load
 $V_{IN} = 12\text{ V}$, $C_L = 220\text{ }\mu\text{F}$, $C_{SS} = 47\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 30 - Turn On by EN Into OCP Load
 $V_{IN} = 12\text{ V}$, $R_L = 2\text{ }\Omega$, $C_L = 220\text{ }\mu\text{F}$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 28 - Turn On Into Output Short
 $V_{IN} = 12\text{ V}$, $C_{SS} = 133\text{ nF}$, $I_{LIM} = 1.74\text{ k}\Omega$




Fig. 31 - Output Short With a 2 Ω Load
 $V_{IN} = 12\text{ V}$, $R_L = 2\text{ }\Omega$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 29 - Turn On Into Output Short, Auto-Retry
 $V_{IN} = 12\text{ V}$, $C_{SS} = 133\text{ }\mu\text{F}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 32 - Over Current Protection
Increase Load Current Slowly
 $V_{IN} = 12\text{ V}$, $C_L = 220\text{ }\mu\text{F}$, $C_{SS} = 133\text{ nF}$, $R_{LIM} = 1.74\text{ k}\Omega$




Fig. 33 - Over Voltage Protection
 $R_L = 12 \Omega$, $C_L = 100 \mu F$, $C_{SS} = 27 \text{ nF}$, $R_{LIM} = 1.74 \text{ k}\Omega$,
OVP Set to 15.6 V

OPERATION

The SIPQ32434A and SIPQ32434B are 33 m Ω switches designed to operate in the 2.8 V to 22 V range. The V_{IN} maximum DC tolerance is 28 V.

The devices start their operation by checking the V_{IN} , V_{OUT} , OVP, and EN / UVLO pins. When the voltages are within the operation ranges, the PGD open drain switch is off. The PGD is high through an external pull high resistor. A high level on the EN / UVLO pin turns on the soft start current source charging C_{SS} and enables internal MOSFET gate driver control the V_{OUT} to follow SS voltage at 9 times ratio. In case of OCP during soft start, the switch current will be regulated to the set current limit level.

After a successful turn-on sequence, the device now actively monitors its load current, input voltage, and protects the load from harmful over-current, and over-voltage conditions. A built-in thermal sense circuit will detect junction over temperature and shut down the switch for safety.

SWITCH ON / OFF, AND UNDER-VOLTAGE LOCKOUT PROTECTION - UVLO

EN / UVLO pin controls the on / off of the power switch. When EN / UVLO is at a logic high the switch is on. When EN / UVLO is at a logic low, the switch is off.

The SIPQ32434A and SIPQ32434B implement under-voltage protection on the EN / UVLO to turn off the output. It is a user-defined under-voltage protection setting to flexibly select the proper minimum applied voltage for the downstream load or the device's proper operation.

The diagram shows how a resistor divider from supply to GND can be used to set the UVLO set point for a given voltage supply level.




Fig. 34

The resistors must be sized large enough to minimize the constant leakage from supply to ground through the resistor divider network. At the same time, keep the current through the resistor network sufficiently larger than the leakage current on the EN / UVLO pin to minimize the error in the resistor divider ratio.

$$R_{EN1} = \frac{R_{EN2}(V_{IN} - V_{UVPR})}{V_{UVPR}}$$

Where V_{UVPR} is 1.25 V.

UVLO turn off delay (T_{OFF_DLY}) is typically 550 μ s and turn on delay T_{ON_DLY} is typically 500 μ s.




Fig. 35 - Switching Times

INRUSH CURRENT, AND OVER-CURRENT PROTECTION

The SIPQ32434A and SIPQ32434B incorporate two protections against over-current:

- Adjustable slew rate (SR) for inrush current control
- Adjustable over-current protection / active current limit to protect against overload conditions

The over-current protection (OCP) is active also during soft start. The over-current protection circuit controls the switch impedance to limit the current to the level programmed by the R_{SET} resistor.

If the over-current condition persists for more than 6 ms (typ.), the switch shuts off and alert the drain FLG is asserted, pulling the pin to GND.

SLEW RATE CONTROL

An inrush current happens when the switch turns on into a large output capacitance. If the inrush current is not controlled, it can damage the input connectors and / or cause the system power supply to droop, leading to unexpected restarts elsewhere in the system.

The SIPQ32434A and SIPQ32434B provide integrated output slew rate control to manage the inrush current during start-up. This is achieved by forcing the V_{OUT} to follow the voltage on a soft start capacitor. A constant current source of 5 μA charges the C_{SS} , generating a linear ramp up voltage on C_{SS} .

$$V_{OUT} = 9 \times V_{SS}$$

The inrush current is proportional to the load capacitance and rising slew rate. The following equations can be used to calculate the C_{SS} and slew rate required to limit the inrush current (I_{INRUSH}) for a given load capacitance (C_{OUT}):


$$SR (V/ms) = \frac{I_{INRUSH} (mA)}{C_{OUT} (\mu F)}$$

$$SR = \frac{I_{SS}}{C_{SS}} \times 9$$

$$T_{SS} = \frac{V_{IN}}{SR} = V_{IN} \times \frac{C_{OUT} (\mu F)}{I_{INRUSH} (mA)}$$

Inrush current should be controlled well below 20 % of set current limit, and within the device SOA.

The fastest output slew rate is achieved by leaving the soft start pin open.



PGD is pulled through a resistor to an external voltage source

Fig. 36

CURRENT LIMIT SETTING

The SIPQ32434A and SIPQ32434B actively monitor the current flow through the switch and provide a quick response to over-current conditions by actively regulating the current to a set limit. The current limit is set by connecting a resistor between the I_{LIM} pin and GND. R_{SET} can be calculated by the following formula for a desired current limit:

$$I_{LIM} = \frac{V_{OCP}}{R_{SET}} \times 20\,600$$

V_{OCP} is 0.6 V.

When the load current exceeds the threshold (I_{LIM}), the parts respond within 1 μ s (typ.) to turn off the switch and then regulate the switch gate voltage to limit the output current to the set I_{LIM} level. During this brief period before the over-current protection circuit is engaged, the parts will see a surge current, especially under a severe output short condition. The magnitude of the surge current developed during the period when the over-current protection is not engaged is determined by impedance in the loop from the input current source to ground and the response time. This impedance is the sum total of the current source impedance, the path resistance and inductance, and the load impedance.

If the over-current condition persists for more than 6 ms / typ., the switch shuts off. When V_{OUT} falls below 95 % of V_{IN} , the PGD is pulled low. The device will exit current limiting when the load current falls below I_{LIM} before the end of the current limit period. The control circuit will increase the gate drive in the same manner as the soft start when the switch exits from the current limit mode.

The I_{LIMIT} / I_{MON} pin can also be used for current reporting. The output path should be of high impedance to prevent any disruption to the current limit circuitry.

The current limit mode could result in excessive power on the switch, which increases the T_J quickly. The SIPQ32434A and SIPQ32434B have OTP, providing an enhanced level of protection.

Once the device is off due to OCP or OTP faults, the SIPQ32434A stays in the latch-off state and the SIPQ32434B auto-retries after 32 times of the programmed soft start time. They can be reset by toggling V_{IN} or EN / UVLO.




Fig. 37 - Over-Current Protection




Fig. 38 - Turn On Into Over-Current Load

OVER-VOLTAGE PROTECTION (OVP)

The SIPQ32434A and SIPQ32434B implement overvoltage protection (OVP) on both the V_{IN} and OVP pins to protect the output load in the event of an input over-voltage. When the input exceeds the over-voltage protection thresholds $V_{OVP(R)}$ or the I_{NOVP} , which is typically 24 V, the device turns off the output within t_{OVP} , while the open drain PGD asserts in the meantime. As long as an over-voltage condition is present on the input, the device stays disabled with the output turned off. Over-voltage is a non-latchable fault. Once the input voltage returns to the normal operating range, the device attempts to start up normally.




Fig. 39

$$\frac{R_{OVP1}}{R_{OVP2}} = \frac{V_{IN(OVP)} - 1.2 \text{ V}}{1.2 \text{ V}}$$

OVP voltage divider resistors total resistance should not be over 2.5 MΩ.




Fig. 40 - Over-Voltage Protection

OTP, OVER-TEMPERATURE PROTECTION

Over-temperature protection turns off the power switch when the die temperature reaches the OTP threshold of 165 °C. The hysteresis is 45 °C. When the die temperature drops below 120 °C, it is allowed to turn on again.

PGD, POWER GOOD REPORTING

PGD is an open drain output. Connect an external pull-up resistor to 3.3 V or 5 V.. It is asserted low when V_{OUT} is below 95 % of V_{IN} , an over-current, over-voltage, or over-temperature fault condition occurs.

INPUT CAPACITOR

A 2.2 μF or larger C_{IN} is recommended. It should be placed as physically close to the device's input pins and ground to be effective to minimize transients on the input. Ceramic capacitors are recommended over tantalum because of their ability to withstand input current surges from low impedance sources such as batteries. For hot-plug applications, where input path inductance is negligible, this input capacitor can be minimized or eliminated.

OUTPUT CAPACITOR

The SIP32433A and SIP32433B do not require an output capacitor for proper operation. Still, a proper value C_{OUT} is recommended to accommodate load transient per circuit design requirements. There are no ESR or capacitor type requirements.

Protection

LAYOUT GUIDELINES

The SIPQ32434A and SIPQ32434B are protection switches designed to maintain a constant output load current upon over-current fault. Optimized layout with efficient heat sinking is critical. It is recommended to put as much copper as possible to the devices' central exposed pad which is connected to ground. Connect all ground planes with all possible thermal VIAs.

The circuit setting components should be laid close to their connection pins. The components include current limit setting resistor, soft start setting capacitor, and resistors connected to EN / UVLO and OVP pins.

Protection devices such as input TVS or output Schottky diodes must be located close the pins to be protected and routed with short traces to reduce inductance.

Below is a layout example.




Fig. 41

**PRODUCT SUMMARY**

Part number	SiPQ32434A	SiPQ32434B
Description	6 A, 33 m Ω , 2.8 V to 22 V eFuse with accurate current limit and programmable OVP	6 A, 33 m Ω , 2.8 V to 22 V eFuse with accurate current limit and programmable OVP
Configuration	Single	Single
Slew rate time (μ s)	Adjustable	Adjustable
On delay time (μ s)	190	190
Input voltage min. (V)	2.8	2.8
Input voltage max. (V)	28	28
On-resistance at input voltage min. (m Ω)	33	33
On-resistance at input voltage max. (m Ω)	33	33
Quiescent current at input voltage min. (μ A)	180	180
Quiescent current at input voltage max. (μ A)	250	250
Output discharge (yes / no)	N	N
Reverse blocking (yes / no)	N	N
Continuous current (A)	6	6
Package type	DFN33 10L wettable flank	DFN33 10L wettable flank
Package size (W, L, H) (mm)	3.0 x 3.0 x 0.9	3.0 x 3.0 x 0.9
Status code	1	1
Product type	Slew rate, current limit	Slew rate, current limit
Applications	Automotive infotainment, ADAD and auto pilot, cameras and sensors, USB hubs, holdup power switching, power management	Automotive infotainment, ADAD and auto pilot, cameras and sensors, USB hubs, holdup power switching, power management

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package / tape drawings, part marking, and reliability data, see www.vishay.com/ppg?62036.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.