8501XC2

NEMA Control Relay, Type X, overlapping contact cartiridge, 10A resistive at 600 VAC, 1 NO or 1 NC contact



Main

- Triairi	
Range of Product	8501X
Relay Type	Control relay
Product or Component Type	Overlapping contact cartridge

Complementary

Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508	
The state of the s	3 A 240 V AC inductive control circuit UL 508	
	1.5 A 480 V AC inductive control circuit UL 508	
	1.2 A 600 V AC inductive control circuit UL 508	
	10 A <= 600 V AC resistive control circuit UL 508	
	1.1 A 125 V DC inductive control circuit UL 508	
	4 A 125 V DC resistive control circuit UL 508	
[lcm] rated short-circuit making capacity	60 A 120 V AC inductive control circuit UL 508	
	30 A 240 V AC inductive control circuit UL 508	
	15 A 480 V AC inductive control circuit UL 508	
	12 A 600 V AC inductive control circuit UL 508	
	10 A <= 600 V AC resistive control circuit UL 508	
	1.1 A 125 V DC inductive control circuit UL 508	
	4 A 125 V DC inductive control circuit UL 508	
Contacts Configuration	1 NO 1 overlapping contact cartridge	

Environment

Product Certifications	UL recognized E78403 CCN NKCR2	
	CE	
	CSA LR60905 class 3211 02	

Ordering and shipping details

Category	21159-8501 X ACCESSORIES	
Discount Schedule	CP2	
GTIN	785901537106	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.02 lb(US) (0.01 kg)	
Returnability	No	
Country of origin	MX	

Packing Units

Package 1 Height	8.89 in (22.581 cm)
Package 1 width	3.50 in (8.890 cm)
Package 1 Length	22.58 in (57.355 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information

Contractual warranty

Warranty 18 months
