




Clock Oscillator SMD-version

+3.3 V

part no.	12.90329
model	KXO-V94T
frequency	32.0 MHz
frequency stability -40° ~ +85°C	±50 ppm
operating temperature	-40° ~ +85°C
storage temperature	-55° ~ +100°C
symmetry	45 % ~ 55 % at 50 % V _{DD} level
rise & fall time max.	5 ns (10 % V _{DD} ~ 90 % V _{DD} level)
"0" level max.	V _{OL} : 10 % V _{DD}
"1" level min.	V _{OH} : 90 % V _{DD}
supply voltage V _{DD}	+3.3 V DC ±5 %
tri-state control voltage (Pin#1)	V _{IH} : V _{DD} x 0.7 min. V _{IL} : V _{DD} x 0.3 max.
supply voltage	+1.8 V ~ +3.6 V
supply current range	3.4 mA typ., 7.0 mA max.
output load max.	15 pF (HCMOS)
start up time max.	10 ms
disable delay time max.	200 ns
enable delay time max.	10 ms
stand by current max.	10 µA (Pin #1 = V _{IL})
contents of reel	1000 pcs.


Dimensions (mm):




PIN	Connection
1	"L" (0V) "H" or OPEN
2	GND
3	Z OUTPUT
4	V _{DD}

Z: high impedance


Suggested soldering pad:




Test circuit:




Output Waveform:



Reflow soldering condition:



Tape specification:



reel diameter 178 mm