



3.2x2.5mm 32.768 kHz SMD Oscillator

O3HF

(former F32K Series)

DATASHEET

- HCMOS Output
- Stability of -170 ~ +10 PPM
- Temperature Range -40°C to +85°C

ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	32.768 kHz
Temperature Range	
Operating (T _{OPR})	-40 ~ +85°C
Storage (T _{STG})	-55 ~ +125°C
Frequency Tolerance @ 25°C	+5 ± 20 PPM
Frequency Stability, ref. 25°C	
-20°C ~ +70°C	-120 ~ +10 PPM
-40°C ~ +85°C	-170 ~ +10 PPM
Supply Voltage (V _{DD})	3.3V ± 10% (Std.) 1.5V ~ 5.5V (Usable)
Input Current (I _{DD}) (no load)	1.5 µA
Output Symmetry (50% V _{DD})	40% ~ 60%
Rise/Fall Time (T _R /T _F) (20%/80% V _{DD} Levels)	200 nS
Output Voltage (V _{OL}) (V _{OH})	0.4V Max V _{DD} - 0.4V Min
Output Load (HCMOS)	15 pF
Start-up Time (T _s) (V _{DD} = 1.5 ~ 5.5V, T _a = -40°C ~ +85°C)	1 Second
Maximum Soldering Temp / Time	260°C / 10 Seconds x 2 cycles
Moisture Sensitivity Level (MSL) per J-STD-033	N/A
Termination Finish	Au (0.3~1µm) over Ni (1.27~8.89µm)
Seal Method	Seam
Lead (Pb) Free	Yes, no exemptions
RoHS Compliant	Yes
REACH Compliant (latest version)	Yes

ENABLE / DISABLE FUNCTION

Pin1	Output (pin 3)
OPEN ¹	Active
'1' Level V _{IH} ≥ 80%V _{DD}	Active
'0' Level V _{IL} ≤ 20%V _{DD}	High Z


¹ An internal pull-up resistor from pin 1 to pin 4 allows active output if pin 1 is left open

Notes:

*A 0.01µF capacitor should be placed between V_{DD} (Pin 4) and GND (Pin2) to minimize power supply line noise.

*Dimensional drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary



© Copyright 2020 Fox Electronics. All rights reserved

Title / Description: O3HF SERIES STANDARD SPECIFICATIONS			
Drawing Number: 100565		Size: A	
Part Number:		Case: 61429	
Draftsperson: MAJ	Approved: BEC	Revision Date: 10/5/2020	




3.2x2.5mm 32.768 kHz SMD Oscillator

O3HF

(former F32K Series)

DATASHEET

Tape Specifications (millimeters)							Reel Specifications (millimeters)						
A	B	C	D	E	F	Reel Qty. Options	G	H	I	J	K	L	M
Ø1.5	4.0	4.0	3.5	8.0	1.4	-T3 = 3,000* *default -T1 = 1,000	2.5	Ø13	Ø22	Ø60	Ø178	8.0	1.6



Available Options & Part Identification

Example: **F O3HF C Y M 0.032768**

F	O3HF	C	Y	M	0.032768
Fox	Model Number	Voltage C = 3.3V ± 10%	Stability Y = -170 ~ +10PPM	Operating Temperature M = -40 to +85°C	Frequency (MHz)



Corporate Headquarters

5570 Enterprise Parkway
Fort Myers, FL 33905
<http://www.FOXONLINE.com>

Sales

1-888-GET-2-FOX (1-888-438-2369)
or
1-239-693-0099
<http://www.FOXONLINE.com/repdisty>

Tech Support

<http://www.FOXONLINE.com/email>

Product use: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice.

Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third party owners.



© Copyright 2020 Fox Electronics. All rights reserved

Title / Description: O3HF SERIES STANDARD SPECIFICATIONS	
Drawing Number: 100565	Size: A
Part Number:	Case: 61429
Draftsperson: MAJ	Approved: BEC
Revision Date: 10/5/2020	