

Additional Resources: Product Page

date 09/11/2024

page 1 of 4

MODEL: CMS-3648-150SP | **DESCRIPTION:** SPEAKER

FEATURES

- 50 ohm
- rated 1.0 W
- solder pads





SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
input power			1	1.5	W
impedance	at 1.2 kHz	42.5	50	57.5	Ω
resonant frequency (Fo)		464	580	696	Hz
frequency response		400		6,000	Hz
sound pressure level	at 1.0 W, 50 cm, avg 0.8, 1.0, 1.2, 1.5 kHz	86	89	92	dB
distortion	at 1.0 kHz, 1.0 W			5	%
buzz, rattle, etc.	must be normal at sine wave			7.07	V
polarity	cone moves forward w/ positive dc current to "+" terminal				
dimensions	Ø36 x 4.8				mm
magnet	Nd-Fe-B				
frame material	iron				
cone material	PEI				
terminal	solder pads				
weight			8.6		g
operating temperature		-20		55	°C
storage temperature		-25		60	°C
hand soldering	for maximum 2 seconds	360		380	°C
RoHS	yes				


Notes:


1. All specifications measured at 15~35°C, humidity at 25~75%, unless otherwise noted.


MECHANICAL DRAWING

units: mm tolerance: ±0.2 mm










RESPONSE CURVES

Frequency Response Curve

Test Conditions: 7.07 V / 50 cm



Additional Resources: Product Page

SAME SKY | MODEL: CMS-3648-150SP | DESCRIPTION: SPEAKER

date 09/11/2024 | page 4 of 4

REVISION HISTORY

rev.	description	date
1.0	initial release	07/06/2023
1.01	CUI Devices rebranded to Same Sky	09/11/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.