



Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP68



Hexagonal nut for chassis plugs and sockets (spare part)









Environmental conditions					
Temperature range		-40 °C/+85 °C			
Materials					
Hexagonal nut		CuZn, nickel-plated			
Mechanical data					
Tightening torque nut		1-3 Nm			
Associated produ	cts				
Accessories					
☞ 030398	☑ 0304	C 0304-1			
☞ 0304-2	☞ 0305	C 0305-1			
C™ 0305-1 U	☑ 0305-2	C 0306			
C 0306-1	☞ 0306-2	C 0307			
C 0307-1	C [*] 0307-2	C 030798-1			

🗗 030799-2

C 0314-2

🗗 0315-1 U

C^{*} 0316-1

C 0317-1

C^{*} 0363

🖙 KFV ... C

🗗 KGV ... C

🗗 SGR

🗗 031798-2

C 0314

C 0315

C 0315-2

C 0316-2

C 0317-2

🕑 KFR

🗗 KGR

🗗 SFV

🗗 SGV

C 031799-2

☑ 030798-2

C 0314-1

☑ 0315-1 ☑ 0316

C 0317

☞ 0362 ☞ KFV

r KGV r SFV … C

🖻 SGV ... C

🗗 031798-1





Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
0384	-	100	500

Packaging: in a cardboard box