

# Filler plugs - HC-K-BS-M32-BK - 1410754

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Filler plug, plastic, size: M32

Filler plugs



## **Key Commercial Data**

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	8.0 g
Custom tariff number	39269097
Country of origin	Germany

#### Technical data

#### Ambient conditions

Degree of protection	IP65
	IP65
	IP66 (Tightening torque 3.0 Nm)
Ambient temperature (operation)	-30 °C 100 °C

#### General

Type of the screw connection	M32
Material	Polyamide fiberglass reinforced
Seal material	CR
Thread type on connection side	M32
Torque	3 Nm
Flammability rating according to UL 94	НВ
Color	black
	black



# Filler plugs - HC-K-BS-M32-BK - 1410754

## Technical data

#### Standards and Regulations

Flammability rating according to UL 94	НВ

### Classifications

#### eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	23111190

#### **ETIM**

ETIM 4.0	EC000032
ETIM 5.0	EC000723

### UNSPSC

UNSPSC 6.01	30211808
UNSPSC 7.0901	39121408
UNSPSC 11	39121408
UNSPSC 12.01	39121408
UNSPSC 13.2	39121408

## Approvals

#### Approvals

Approvals

EAC

Ex Approvals

Approvals submitted



# Filler plugs - HC-K-BS-M32-BK - 1410754


## Approvals

Approval details

EAC

### Drawings

#### Dimensional drawing



Dimensional drawing

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com