

463BS6

Wall mounted inlet

2CMA167566R1000



Surface Inlet, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Wall mounted inlet
Product ID	2CMA167566R1000
Function	Surface inlet
EAN	7392696675666
Catalog Description	Surface inlet, 6h, 63A, IP44, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421526
E-Number Norway	2417207
E-Number Sweden	E2417207
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	TBS
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	63 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz 60 hertz
Degree of Protection	IP44
Cable Cross-Section	6...25 mm ²
Housing Material	Plastic (PA)
Plug Angle	Angled
Product Group	Tough&Safe

DIMENSIONS

Product Net Width	107 millimetre
Product Net Height	117 millimetre
Product Net Length	237 millimetre
Product Net Depth	237 millimetre
Product Net Weight	0.85 kilogram

PACKAGING

Package Width	152 millimetre
Package Height	265 millimetre
Package Gross Weight	0.94 kilogram
Package Length	120 millimetre
Package Units	box 1 piece