

416BU6

Panel mounted inlet

2CMA193468R1000

Panel mounted inlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, unified flange, straight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red



GENERAL

Product Name	Panel mounted inlet
Product ID	2CMA193468R1000
Function	Panel mounted inlet
EAN	7392696934688
Catalog Description	Inlet, panel mounting, 6h, 16A, IP44, unified flange, straight, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2420205
E-Number Norway	2417340
E-Number Sweden	E2417340
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	EBU
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	16 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz 60 hertz
Degree of Protection	IP44
Cable Cross-Section	1.5...4 mm ²
Housing Material	Plastic (PA)
Plug Angle	Straight
Product Group	Easy&Safe

DIMENSIONS

Product Net Width	76 millimetre
Product Net Height	79 millimetre
Product Net Length	81 millimetre
Product Net Depth	81 millimetre
Product Net Weight	0.14 kilogram

PACKAGING

Package Width	138 millimetre
Package Height	345 millimetre
Package Gross Weight	1.4 kilogram
Package Length	158 millimetre
Package Units	box 10 piece