

Style
M8 Plug
3 pin
A-coding

Ratings
Voltage: 60 V
Current: 3 A

Operating Temperature Range
-40~105 °C






Materials
① Insulator: PA66, UL94, HB, black
② Pin: C3604 brass, gold flashing
③ Shell: C3604 brass, nickel plated

Electrical Requirements
Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less

Mechanical Requirements
Life cycle: 1000 mating cycles minimum

Environmental Requirements
Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 24 hrs. Wash parts after test. Maintain mechanical requirements and a contact resistance of less than 10 mΩ.
Waterproof: IP67

Assembly Info
Wire gauge: 24 AWG max



Revision:	Date:	Description:	Prepared:	Notes:	<div>TENSILITY</div> <div> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com </div>		
A	8/17/21	Initial Release	Verified:	RoHS compliant Function test: no open, no short circuit, no intermittent			
			Dimensions are in millimeters. Tolerances: X: ± 0.3 mm X.X: ± 0.1 mm X.XX: ± 0.05 mm	Description: Connector, M8 A-code plug, 3 pin, 8xL 19.2 mm, molding style, solder cup, gold plated, IP67	Size: A	Part number: 50-00675	
					Scale: 2:1		Sheet 1 of 1