

M8 Plug, shielded
4 pin
A-coding

Voltage: 30 V
Current: 3 A

-40 ~ 105 °C


- ① Insulator: PA66, UL 94 HB, black
- ② Pin: C3604 brass, gold flashing
- ③ Nut: C3604 brass, nickel plated
- ④ Shell: C3604 brass, nickel plated
- ⑤ O-ring: Silcione rubber
- ⑥ Epoxy: Epoxy resin

Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less



Life cycle: 1000 mating cycles minimum



Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 24 hrs. Wash parts after test. Maintain mechanical requirements and a contact resistance of less than 10 mΩ.
Waterproof: IP67

Wire gauge: 24 AWG max



Front View
Not to Scale



Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118</p> <p>fax 1.541.323.4202 web tensility.com</p>		
A	8/25/21	Initial Release	Verified:	RoHS compliant			
			Dimensions are in millimeters. Tolerances: X: ± 0.3 mm X.X: ± 0.1 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent			
				Description:	Size:	Part number:	
				Connector, M8 A-code plug, 4 pin, 8xL19.2 mm, panel mount, solder cup, gold plated, IP67	A	54-00291	
				Scale:	2:1	 	Sheet 1 of 1