

BNC Connector Plug, Male Pin 50 Ohms Free Hanging (In-Line), Right Angle Crimp

**RoHS
Compliant**

Stock No.: 9200896C0171

FEATURES

- BNC Plug
- 50 Ohms
- RG-55, 142, 223, 400/U






Product Description

BNC connector has a robust center contact and outer conductor interface. BNC connectors generally work up to 4 GHz and are a cost-effective way of insuring a highly dependable RF Coaxial connection.


General Specifications

Attribute	Value
Connector Style	BNC
Gender	Male
Impedance	50Ω
Mounting Type	Free Hanging (In-Line)
Frequency Range	4 GHz
Body Orientation	Right Angle
Polarity	Normal
Contact Plating	Gold
Body Plating	Nickel
Contact Material	Brass
Voltage Rating	500 V
Temperature Range	-65°C ~ 165°C

Product Drawing



IMPEDANCE: 50 OHMS
WORKING VOLTAGE: 500 VRMS @ SEA LEVEL
FREQUENCY RANGE: 0-4 GHz
INSERTION LOSS: \leq -.3dB @ 3 GHz
VSWR MAX: 1.5:1 @ 3 GHz
FOR RG-55, 55A, 55B, 142, 142A, 142B, 223 & 400/U,
ALPHA 9055, 9055B, 9223, BELDEN 8219, 83242, 84142, 9907
INTERFACE PER MIL-STD-348, SECTION 301.1



SUGGESTED STRIPPING INSTRUCTIONS

SUGGESTED DIES: .213 & .068

Dimensions: Millimeters (Inches)

Part Number Table

Part Number	Description
9200896C0171	BNC Connector Plug, Male Pin 50 Ohms Free Hanging (In-Line), Right Angle Crimp

Important Notice: This data sheet and its contents (the "Information") belong to the members of the EASE group of companies (the "Group") or are licensed to it. No license is granted for the use of it other than for information purposes in connection with the products to which it relates. No license of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate, but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. EASE is the registered trademark of Ease Electronics Co., Limited 2019.