

	1	2	3	4	5	6	7																																																																																																																
A					Technical specifications: Materials: 1. Insulator: Glass-Filled PBT, Color: Grey, UL 94V-0 2. Contact: Copper Alloy Contact plating according DIN41612 performance classes: Performance class I (-1) 500 mating cycles min. 30u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class II (-2) 250 mating cycles min. 15u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class III (blank) 50 mating cycles min. Gold flash on mating side over 50u" Nickel 100u" Sn plating on solder area over 50u" Nickel Other specifications: Contact resistance: 20mOhm max. Insulation resistance: 10 ¹² Ohm min. Current rating: 2A Operating temperature: -40°C to 105°C Operating voltage: 125VAC Test voltage: 1000VAC Packaging: Tray Printing : WSW+WSW part number +datacode(WWYY)			A																																																																																																															
B								B																																																																																																															
C								C																																																																																																															
D					DIN41612 STYLE R MALE INVERSIVE STRAIGHT <table><tr><th colspan="7">ORDERING CODE</th><th colspan="4">CONTACT DETAILS</th></tr><tr><th>Style</th><th>M=Male F=Female</th><th>No of</th><th>Rows loaded</th><th>Pin type</th><th>Plating Class</th><th></th><th>Pin length in mm</th><th>Cross section</th><th>Pin load</th><th>Pin type/direction</th></tr><tr><td>A - R</td><td>M</td><td>xx</td><td>xx</td><td>x</td><td>-</td><td>x</td><td></td><td></td><td></td><td></td></tr></table> Options (if another contact loading option is needed, please contact your sales office) <table><tr><td>A</td><td>R</td><td>M</td><td>96</td><td>abc</td><td>T</td><td>-</td><td>1</td><td>T:</td><td>4.00 (±0.25)</td><td>0.60x0.60(±0.03)</td><td>abc: 3x32</td><td>THT straight (Page 1)</td></tr><tr><td></td><td></td><td></td><td>64</td><td>a+c</td><td>T2.5</td><td></td><td>2</td><td>T2.5:</td><td>2.50 (±0.25)</td><td></td><td>a+c: 2x32</td><td></td></tr><tr><td></td><td></td><td></td><td>32</td><td>a</td><td></td><td></td><td>blank</td><td></td><td></td><td></td><td>a: 1x32</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>WAP</td><td></td><td></td><td>WAB:</td><td>13.00 (±0.20)</td><td>0.64x0.60(±0.03)</td><td></td><td>Wire wrap (Page 2)</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>P</td><td></td><td></td><td>P:</td><td>5.00 (±0.20)</td><td></td><td></td><td>Press-In straight (Page 3)</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>PWAB</td><td></td><td></td><td>PWAB:</td><td>13.00 (±0.20)</td><td></td><td></td><td></td></tr></table>			ORDERING CODE							CONTACT DETAILS				Style	M=Male F=Female	No of	Rows loaded	Pin type	Plating Class		Pin length in mm	Cross section	Pin load	Pin type/direction	A - R	M	xx	xx	x	-	x					A	R	M	96	abc	T	-	1	T:	4.00 (±0.25)	0.60x0.60(±0.03)	abc: 3x32	THT straight (Page 1)				64	a+c	T2.5		2	T2.5:	2.50 (±0.25)		a+c: 2x32					32	a			blank				a: 1x32							WAP			WAB:	13.00 (±0.20)	0.64x0.60(±0.03)		Wire wrap (Page 2)						P			P:	5.00 (±0.20)			Press-In straight (Page 3)						PWAB			PWAB:	13.00 (±0.20)				D
ORDERING CODE								CONTACT DETAILS																																																																																																															
Style								M=Male F=Female	No of	Rows loaded	Pin type	Plating Class		Pin length in mm	Cross section	Pin load	Pin type/direction																																																																																																						
A - R	M	xx	xx	x	-	x																																																																																																																	
A	R	M	96	abc	T	-	1	T:	4.00 (±0.25)	0.60x0.60(±0.03)	abc: 3x32	THT straight (Page 1)																																																																																																											
			64	a+c	T2.5		2	T2.5:	2.50 (±0.25)		a+c: 2x32																																																																																																												
			32	a			blank				a: 1x32																																																																																																												
					WAP			WAB:	13.00 (±0.20)	0.64x0.60(±0.03)		Wire wrap (Page 2)																																																																																																											
					P			P:	5.00 (±0.20)			Press-In straight (Page 3)																																																																																																											
					PWAB			PWAB:	13.00 (±0.20)																																																																																																														
E	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)				<table><tr><th>ROWS</th><th>DIM.A</th><th>DIM.B</th><th>DIM.C</th><th>DIM.D</th></tr><tr><td>3</td><td>95.00</td><td>78.74</td><td>85.20</td><td>90.00</td></tr><tr><td>2</td><td>95.00</td><td>78.74</td><td>85.20</td><td>90.00</td></tr><tr><td>3</td><td>54.40</td><td>38.10</td><td>44.60</td><td>50.00</td></tr><tr><td>2</td><td>54.40</td><td>38.10</td><td>44.60</td><td>50.00</td></tr></table>			ROWS	DIM.A	DIM.B	DIM.C	DIM.D	3	95.00	78.74	85.20	90.00	2	95.00	78.74	85.20	90.00	3	54.40	38.10	44.60	50.00	2	54.40	38.10	44.60	50.00	E																																																																																						
ROWS								DIM.A	DIM.B	DIM.C	DIM.D																																																																																																												
3								95.00	78.74	85.20	90.00																																																																																																												
2	95.00	78.74	85.20	90.00																																																																																																																			
3	54.40	38.10	44.60	50.00																																																																																																																			
2	54.40	38.10	44.60	50.00																																																																																																																			
F	F																																																																																																																						
G	RoHS compliant Unit: mm File No.: E198287		<table><tr><th>Scale</th><th>Free</th></tr><tr><td>TOLERANCE</td><td></td></tr><tr><td>X.</td><td>±X</td></tr><tr><td>X.X</td><td>±0.40</td></tr><tr><td>X.XX</td><td>±0.25</td></tr><tr><td>X.XXX</td><td>±0.15</td></tr><tr><td>DIM</td><td>TOL</td></tr><tr><td>Angle</td><td>±3°</td></tr></table>	Scale	Free	TOLERANCE		X.	±X	X.X	±0.40	X.XX	±0.25	X.XXX	±0.15	DIM	TOL	Angle	±3°	<table><tr><td>⑤</td><td>Update the page 2&3</td><td>21.01.2025</td><td>Winnie</td><td></td><td>Date</td><td>Name</td><td rowspan="2">Description: DIN 41612 Type R / Male / straight</td></tr><tr><td>④</td><td>Add UL E-file No.</td><td>20.05.2021</td><td>Daniel</td><td>Drawn</td><td>27.05.2013</td><td>Winnie</td></tr><tr><td>③</td><td>Add the page 2&3</td><td>30.01.2021</td><td>Winnie</td><td>Approved</td><td>21.01.2025</td><td>Winnie</td><td rowspan="2">ASSMANN WSW-No. A-RMxxxxx-x</td></tr><tr><td>②</td><td>Change to new plant</td><td>17.08.2020</td><td>Winnie</td><td></td><td></td><td></td></tr></table>	⑤	Update the page 2&3	21.01.2025	Winnie		Date	Name	Description: DIN 41612 Type R / Male / straight	④	Add UL E-file No.	20.05.2021	Daniel	Drawn	27.05.2013	Winnie	③	Add the page 2&3	30.01.2021	Winnie	Approved	21.01.2025	Winnie	ASSMANN WSW-No. A-RMxxxxx-x	②	Change to new plant	17.08.2020	Winnie				ASSMANN WSW components	Drawing-No. ASS 5681 CO	rev05	H																																																																	
Scale			Free																																																																																																																				
TOLERANCE																																																																																																																							
X.	±X																																																																																																																						
X.X	±0.40																																																																																																																						
X.XX	±0.25																																																																																																																						
X.XXX	±0.15																																																																																																																						
DIM	TOL																																																																																																																						
Angle	±3°																																																																																																																						
⑤	Update the page 2&3	21.01.2025	Winnie		Date	Name	Description: DIN 41612 Type R / Male / straight																																																																																																																
④	Add UL E-file No.	20.05.2021	Daniel	Drawn	27.05.2013	Winnie																																																																																																																	
③	Add the page 2&3	30.01.2021	Winnie	Approved	21.01.2025	Winnie	ASSMANN WSW-No. A-RMxxxxx-x																																																																																																																
②	Change to new plant	17.08.2020	Winnie																																																																																																																				
H							Customer-No.	SHEET 1 / 3																																																																																																															
	1	2	3	4	5	6	7	SV4824																																																																																																															

