





	1	2	3	4	5	6	7																																																																																																			
A								A																																																																																																		
B	Technical specifications: Materials: 1. Insulator: Glass-Filled PBT, Color: Grey, UL 94V-0 2. Contact: Copper Alloy Contact plating according DIN41612 performance classes: Performance class I (-1) 500 mating cycles min. 30u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class II (-2) 250 mating cycles min. 15u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class III (blank) 50 mating cycles min. Gold flash on mating side over 50u" Nickel 100u" Sn plating on solder area over 50u" Nickel Other specifications: Contact resistance: 20mOhm max. Insulation resistance: 10¹²Ohm min. Current rating: 2A Operating temperature: -40°C to 105°C Operating voltage: 125VAC Test voltage: 1000VAC Packaging: Tray							B																																																																																																		
C								C																																																																																																		
D								D																																																																																																		
E	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05) 							E																																																																																																		
F	<table><tr><th>③</th><th>ROWS</th><th>DIMA</th><th>DIMB</th><th>DIMD</th><th>DIME</th></tr><tr><td>2</td><td>85.20</td><td>88.00</td><td>90.00</td><td>95.00</td><td></td></tr><tr><td>2</td><td>44.60</td><td>47.40</td><td>50.00</td><td>55.00</td><td></td></tr></table>							③	ROWS	DIMA	DIMB	DIMD	DIME	2	85.20	88.00	90.00	95.00		2	44.60	47.40	50.00	55.00		F																																																																																
③	ROWS	DIMA	DIMB	DIMD	DIME																																																																																																					
2	85.20	88.00	90.00	95.00																																																																																																						
2	44.60	47.40	50.00	55.00																																																																																																						
G	<table><tr><th colspan="10">DIN41612 STYLE Q MALE INVERSIVE STRAIGHT</th></tr><tr><th colspan="6">ORDERING CODE</th><th colspan="4">CONTACT DETAILS</th></tr><tr><th></th><th>Style</th><th>M=Male F=Female</th><th>No of pins</th><th>Rows loaded</th><th>Pin type</th><th>Plating Class</th><th>Pin length in mm</th><th>Cross section</th><th>Pin load</th><th>Pin type/direction</th></tr><tr><td>A</td><td>Q</td><td>M</td><td>xx</td><td>xx</td><td>x</td><td>- x</td><td></td><td></td><td></td><td></td></tr></table> Options (if another contact loading option is needed, please contact your sales office) <table><tr><td>⑥</td><td>A</td><td>Q</td><td>M</td><td>64</td><td>ab</td><td>T</td><td>-</td><td>1</td><td>T:</td><td>4.00 (±0.25)</td><td>0.50x0.60(±0.03)</td><td>ab: 2x32</td><td>THT straight(Page 1)</td></tr><tr><td></td><td></td><td></td><td></td><td>32</td><td>a</td><td>T2.5</td><td></td><td>2</td><td>T2.5:</td><td>2.50 (±0.25)</td><td></td><td>a: 1x32</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>P</td><td>blank</td><td></td><td></td><td>P:</td><td>5.00(±0.20)</td><td>0.64x0.60(±0.03)</td><td></td><td>Press-in straight(Page 2)</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>PWAB</td><td></td><td></td><td></td><td>PWAB:</td><td>13.00(±0.20)</td><td></td><td></td><td></td></tr></table>							DIN41612 STYLE Q MALE INVERSIVE STRAIGHT										ORDERING CODE						CONTACT DETAILS					Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Pin length in mm	Cross section	Pin load	Pin type/direction	A	Q	M	xx	xx	x	- x					⑥	A	Q	M	64	ab	T	-	1	T:	4.00 (±0.25)	0.50x0.60(±0.03)	ab: 2x32	THT straight(Page 1)					32	a	T2.5		2	T2.5:	2.50 (±0.25)		a: 1x32							P	blank			P:	5.00(±0.20)	0.64x0.60(±0.03)		Press-in straight(Page 2)						PWAB				PWAB:	13.00(±0.20)				G
DIN41612 STYLE Q MALE INVERSIVE STRAIGHT																																																																																																										
ORDERING CODE						CONTACT DETAILS																																																																																																				
	Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Pin length in mm	Cross section	Pin load	Pin type/direction																																																																																																
A	Q	M	xx	xx	x	- x																																																																																																				
⑥	A	Q	M	64	ab	T	-	1	T:	4.00 (±0.25)	0.50x0.60(±0.03)	ab: 2x32	THT straight(Page 1)																																																																																													
				32	a	T2.5		2	T2.5:	2.50 (±0.25)		a: 1x32																																																																																														
					P	blank			P:	5.00(±0.20)	0.64x0.60(±0.03)		Press-in straight(Page 2)																																																																																													
					PWAB				PWAB:	13.00(±0.20)																																																																																																
H	<table><tr><td rowspan="7">RoHS compliant Unit: mm  File No.: E198287</td><td>Scale</td><td>Free</td><td>⑥</td><td>Update the Pin size to 0.5x0.60 on THT</td><td>19.01.2022</td><td>Winnie</td><td></td><td>Date</td><td>Name</td><td>Description: DIN 41612</td></tr><tr><td>TOLERANCE</td><td></td><td>⑤</td><td>Add page 2</td><td>25.08.2021</td><td>Winnie</td><td>Drawn</td><td>24.05.2013</td><td>Winnie</td><td>Type Q / male / straight</td></tr><tr><td>X.</td><td>±X</td><td>④</td><td>Add Dim.D</td><td>26.07.2021</td><td>Daniel</td><td>Approved</td><td>19.01.2022</td><td>Winnie</td><td>ASSMANN WSW-No.</td></tr><tr><td>X.X</td><td>±0.40</td><td>③</td><td>Update Dim. and add UL E-file No.</td><td>17.05.2021</td><td>Daniel</td><td></td><td></td><td></td><td>A-QMxxxxxx-x</td></tr><tr><td>X.XX</td><td>±0.25</td><td>②</td><td>Change to new plant</td><td>17.08.2020</td><td>Winnie</td><td colspan="4"></td></tr><tr><td>X.XXX</td><td>±0.15</td><td>①</td><td>Modification of Male Pin – see PCN20131612_DIN41612-Arev01</td><td>20.12.2013</td><td>Amy</td><td colspan="2">Drawing-No. ASS 5682 CO</td><td>rev06</td></tr><tr><td>DIM</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td><td>SHEET 1 / 3</td></tr><tr><td>Angle</td><td>±3°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>							RoHS compliant Unit: mm  File No.: E198287	Scale	Free	⑥	Update the Pin size to 0.5x0.60 on THT	19.01.2022	Winnie		Date	Name	Description: DIN 41612	TOLERANCE		⑤	Add page 2	25.08.2021	Winnie	Drawn	24.05.2013	Winnie	Type Q / male / straight	X.	±X	④	Add Dim.D	26.07.2021	Daniel	Approved	19.01.2022	Winnie	ASSMANN WSW-No.	X.X	±0.40	③	Update Dim. and add UL E-file No.	17.05.2021	Daniel				A-QMxxxxxx-x	X.XX	±0.25	②	Change to new plant	17.08.2020	Winnie					X.XXX	±0.15	①	Modification of Male Pin – see PCN20131612_DIN41612-Arev01	20.12.2013	Amy	Drawing-No. ASS 5682 CO		rev06	DIM	TOL	Id.	Modification	Date	Name	Customer-No.		SHEET 1 / 3	Angle	±3°								H																				
RoHS compliant Unit: mm  File No.: E198287	Scale	Free	⑥	Update the Pin size to 0.5x0.60 on THT	19.01.2022	Winnie			Date	Name	Description: DIN 41612																																																																																															
	TOLERANCE		⑤	Add page 2	25.08.2021	Winnie	Drawn		24.05.2013	Winnie	Type Q / male / straight																																																																																															
	X.	±X	④	Add Dim.D	26.07.2021	Daniel	Approved		19.01.2022	Winnie	ASSMANN WSW-No.																																																																																															
	X.X	±0.40	③	Update Dim. and add UL E-file No.	17.05.2021	Daniel					A-QMxxxxxx-x																																																																																															
	X.XX	±0.25	②	Change to new plant	17.08.2020	Winnie																																																																																																				
	X.XXX	±0.15	①	Modification of Male Pin – see PCN20131612_DIN41612-Arev01	20.12.2013	Amy	Drawing-No. ASS 5682 CO		rev06																																																																																																	
	DIM	TOL	Id.	Modification	Date	Name	Customer-No.		SHEET 1 / 3																																																																																																	
Angle	±3°																																																																																																									
	1	2	3	4	5	6	7	SV4824																																																																																																		

