






	1	2	3	4	5	6	7																																																																																		
A	   				Technical specifications: Materials: 1. Insulator: Glass-Filled PBT, Color: Grey, UL 94V-0 2. Contact: Copper Alloy Contact plating according DIN41612 performance classes: Performance class I (-1) 500 mating cycles min. 30u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class II (-2) 250 mating cycles min. 15u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class III (blank) 50 mating cycles min. Gold flash on mating side over 50u" Nickel 100u" Sn plating on solder area over 50u" Nickel Other specifications: Contact resistance: 20mOhm max. Insulation resistance: 10¹² Ohm min. Current rating: 2A Operating temperature: -40°C to 105°C Operating voltage: 125VAC Test voltage: 1000VAC Packaging: Tray				A																																																																																
B					B																																																																																				
C					C																																																																																				
D					D																																																																																				
E	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05) 				<table><tr><th colspan="10">DIN41612 STYLE HALF Q FEMALE INVERSE RIGHT-ANGLE</th></tr><tr><th colspan="8">ORDERING CODE</th><th colspan="2">CONTACT DETAILS</th></tr><tr><th>Style</th><th>M=Male F=Female</th><th>No of</th><th>Rows loaded</th><th>Pin type</th><th>Plating Class</th><th>Board lock</th><th>Pin length in mm</th><th>Cross section</th><th>Pin load</th></tr><tr><td>A - HQ</td><td>F</td><td>XX</td><td>XX</td><td>X</td><td>-</td><td>X</td><td>X</td><td></td><td></td></tr><tr><th colspan="10">Options (if another contact loading option is needed, please contact your sales office)</th></tr><tr><td>A - HQ</td><td>F</td><td>32</td><td>ab</td><td>R</td><td>-</td><td>1</td><td>MC1</td><td>R:</td><td>3.00 (±0.25)</td></tr><tr><td></td><td></td><td>16</td><td>a</td><td></td><td></td><td>2</td><td>blank</td><td></td><td>0.60x0.60(±0.03)</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>blank</td><td></td><td></td><td>ab: 2x16 a: 1x16</td></tr></table>				DIN41612 STYLE HALF Q FEMALE INVERSE RIGHT-ANGLE										ORDERING CODE								CONTACT DETAILS		Style	M=Male F=Female	No of	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load	A - HQ	F	XX	XX	X	-	X	X			Options (if another contact loading option is needed, please contact your sales office)										A - HQ	F	32	ab	R	-	1	MC1	R:	3.00 (±0.25)			16	a			2	blank		0.60x0.60(±0.03)							blank			ab: 2x16 a: 1x16	E
DIN41612 STYLE HALF Q FEMALE INVERSE RIGHT-ANGLE																																																																																									
ORDERING CODE								CONTACT DETAILS																																																																																	
Style	M=Male F=Female	No of	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load																																																																																
A - HQ	F	XX	XX	X	-	X	X																																																																																		
Options (if another contact loading option is needed, please contact your sales office)																																																																																									
A - HQ	F	32	ab	R	-	1	MC1	R:	3.00 (±0.25)																																																																																
		16	a			2	blank		0.60x0.60(±0.03)																																																																																
						blank			ab: 2x16 a: 1x16																																																																																
F	F																																																																																								
G	RoHS compliant Unit: mm  US File No.: E198287				Scale	Free				Date	Name	Description: DIN 41612 Type Half Q / Female / R/A	G																																																																												
					TOLERANCE					Drawn	17.05.2017	Winnie																																																																													
					X.	±X	③	Add UL E-file No.	20.05.2021	Daniel	Approved	20.05.2021	Daniel	ASSMANN WSW-No.																																																																											
					X.X	±0.40	②	Add page 2	25.02.2021	Winnie				A-HQFxxxxR-x																																																																											
					X.XX	±0.25	①	Change to new plant	17.08.2020	Winnie	ASSMANN WSW components																																																																														
					X.XXX	±0.15	①	Drawn	17.05.2017	Winnie																																																																															
H					DIM	TOL	①	Id.	Modification	Date	Name	Drawing-No. ASS 7593 CO	rev03																																																																												
	Angle	±3°						Customer-No.	SHEET 1 / 2																																																																																
	1	2	3	4	5	6	7																																																																																		

