
















	1	2	3	4	5	6	7						
A	 Circuit 1  PCB LAYOUT  PIN 0.50 SQ  TYPE1  TYPE2  ⑦ Notes: Insulator Material: Nylon 66, White UL94V-0; Contact Pin: Brass, Tin over Nickel; Voltage Rating: 100V AC,DC; Current Rating: 2A AC, DC; Insulation Resistance: 1000MΩ Min; Withstanding Voltage: 800V AC/minute; Operation Temperature: -40°C to +105°C; Packing: Bag ⑧ Order Code:A-WBP-K001EG-xxTBxx 01:TYPE 1 UL No.:E198287 ⑨ 02:TYPE 2							A					
B								B					
C								C					
D								D					
E								E					
F								F					
G	RoHS compliant Unit:mm		Scale	Free	⑫	Add UL E-No. on page 5 and remove UL E-No. from page 4	24.07.2022	Peter		Date	Name	Description: Wire to board Wafer connector Pitch 2.0mm 180° THT	
TOLERANCE			⑪	Update the dimension	07.02.2024	Winnie	Drawn	21.01.2021	Segal	ASSMANN WSW-No. A-WBP-K001EG-xxTB01			
X.			±0.35	⑩	Update the dimension and tolerance	03.07.2024	Peter	Approved	24.07.2024				Peter
X.X			±0.25	⑨	Add UL E-No. on page 1,2,4	03.11.2022	Peter						
X.XX			±0.20	⑧	Add P/N and the page 3	03.11.2022	Peter	ASSMANN WSW components A company of BCS					Drawing-No. ASS 8874 CO
X.XXX			±0.15	⑦	Update	22.04.2022	Daniel				Customer-No.		SHEET 2 / 8
DIM			TOL	Id.	Modification	Date	Name						
			Angle	TOL									
H	1	2	3	4	5	6	7						

	1	2	3	4	5	6	7							
A	⑧   Notes: Insulator Material: PA46, Natural,UL94V-0; Contact Pin: Brass, Tin over Nickel; Voltage Rating: 100V AC,DC; Current Rating: 2.0A; Insulation Resistance: 1000MΩ Min; Withstanding Voltage: 800V AC/minute; Contact Resistance: 20mΩ Max Operation Temperature: -40°C to +105°C; Packing: PE bag Soldering Temperature: +360°C,2-3S Order code:A-WBP-K001EG-xxTBxx 03:TYPE 1 04:TYPE 2 Recommended P.C.B Layout (Top Side) (PCB Board Tolerance±0.05)   							A						
B								B						
C								C						
D								D						
E								E						
F								F						
G	RoHS compliant Unit:mm		Scale	Free	⑫	Add UL E-No. on page 5 and remove UL E-No. from page 4	24.07.2022	Peter		Date	Name	Description: Wire to board Wafer connector Pitch 2.0mm 180° THT		G
TOLERANCE			⑪	Update the dimension	07.02.2024	Winnie	Drawn	21.01.2021	Segal					
X.			±0.35	⑩	Update the dimension and tolerance	03.07.2024	Peter	Approved	24.07.2024	Peter	ASSMANN WSW-No. A-WBP-K001EG-xxTBxx			
			X.X	±0.25	⑨	Add UL E-No. on page 1,2,4	03.11.2022	Peter				Drawing-No. ASS 8874 CO		H
			X.XX	±0.20	⑧	Add P/N and the page 3	03.11.2022	Peter	ASSMANN WSW components A company of BCS			rev12		
			X.XXX	±0.15	⑦	Update	22.04.2022	Daniel			Customer-No.		SHEET 3 / 8	
H			DIM	TOL										
			Angle	TOL	Id.	Modification	Date	Name						
	1	2	3	4	5	6	7							



	1	2	3	4	5	6	7							
A	  Notes: ⑦ Insulator Material: Nylon6T, color natural, UL94V-0; Contact Pin: Brass, Tin over Nickel; Voltage Rating: 100V AC,DC; Current Rating: 2A AC, DC; Insulation Resistance: 1000MΩ Min; Withstanding Voltage: 800V AC/minute; Operation Temperature: -40°C to +105°C; Packing: Tape&Reel. PCB LAYOUT  							A						
B								B						
C								C						
D								D						
E								E						
F								F						
G	RoHS compliant Unit:mm		Scale	Free	⑫	Add UL E-No. on page 5 and remove UL E-No. from page 4	24.07.2022	Peter		Date	Name	Description: Wire to board Wafer connector Pitch 2.0mm 90° SMT		G
TOLERANCE			⑪	Update the dimension	07.02.2024	Winnie	Drawn	21.01.2021	Segal					
X.			±0.35	⑩	Update the dimension and tolerance	03.07.2024	Peter	Approved	24.07.2024	Peter				
			X.X	±0.25	⑨	Add UL E-No. on page 1,2,4	03.11.2022	Peter				ASSMANN WSW-No. A-WBP-K001EA-xxSR01		H
			X.XX	±0.20	⑧	Add P/N and the page 3	03.11.2022	Peter	ASSMANN WSW components A company of BCS		Drawing-No.	ASS 8874 CO	rev12	
			X.XXX	±0.15	⑦	Update	22.04.2022	Daniel			Customer-No.	SHEET	4 / 8	
			DIM	TOL										
			Angle	TOL	Id.	Modification	Date	Name						
H	1	2	3	4	5	6	7							

	1	2	3	4	5	6	7	
A								A
B								B
C								C
D								D
E								E
F								F
G								G
H								H

				Notes: ⑦ Insulator Material: Nylon6T, color natural, UL94V-0; Contact Pin: Brass, Tin over Nickel; Voltage Rating: 100V AC,DC; Current Rating: 2A AC, DC; Insulation Resistance: 1000MΩ Min; Withstanding Voltage: 800V AC/minute; Operation Temperature: -40°C to +105°C; Packing: Tape&Reel.	
				PCB LAYOUT	





RoHS compliant Unit:mm ⑫ File No.: E198287	Scale	Free	⑫	Add UL E-No. on page 5 and remove UL E-No. from page 4	24.07.2022	Peter		Date	Name	Description: Wire to board Wafer connector Pitch 2.0mm 180° SMT	
	TOLERANCE		⑪	Update the dimension	07.02.2024	Winnie	Drawn	21.01.2021	Segal		
	X.	±0.35	⑩	Update the dimension and tolerance	03.07.2024	Peter	Approved	24.07.2024	Peter		
	X.X	±0.25	⑨	Add UL E-No. on page 1,2,4	03.11.2022	Peter				ASSMANN WSW-No. A-WBP-K001EG-xxSR01	
	X.XX	±0.20	⑧	Add P/N and the page 3	03.11.2022	Peter			Drawing-No. ASS 8874 CO		rev12
	X.XXX	±0.15	⑦	Update	22.04.2022	Daniel			Customer-No.		SHEET 5 / 8
	DIM	TOL	Id.	Modification	Date	Name					
Angle	TOL										

1	2	3	4	5	6	7	
---	---	---	---	---	---	---	--



Notes:

⑦ Insulator Material:	Nylon6T, color natural, UL94V-0;
Contact Pin:	Brass, Tin over Nickel;
Voltage Rating:	100V AC,DC;
Current Rating:	2A AC, DC;
Insulation Resistance:	1000MΩ Min;
Withstanding Voltage:	800V AC/minute;
Operation Temperature:	-40°C to +105°C;
Packing:	Tape&Reel.



PCB LAYOUT

	1	2	3	4	5	6	7	
A								

	1	2	3	4	5	6	7									
A	Notes: Material: Phosphor Bronze, Tin over Nickel; Voltage Rating: 100V AC, DC; Current Rating: 2A AC, DC; Contact Resistance: 10mΩ Max; Withstanding Voltage: 800V AC/minute; Operation Temperature: -40°C to +105°C; Wire Range: #24-#30; Packing: Reel							A								
B								B								
C								C								
D								D								
E								E								
F								F								
G	RoHS compliant Unit:mm		Scale	Free	⑫	Add UL E-No. on page 5 and remove UL E-No. from page 4	24.07.2022	Peter		Date	Name	Description: Wire to board Terminal Pitch 2.0mm 180°		G		
			TOLERANCE		⑪	Update the dimension	07.02.2024	Winnie	Drawn	21.01.2021	Segal					
			X.	±0.35	⑩	Update the dimension and tolerance	03.07.2024	Peter	Approved	24.07.2024	Peter	ASSMANN WSW-No. A-WBT-K001EG-01CR01				
			X.X	±0.25	⑨	Add UL E-No. on page 1,2,4	03.11.2022	Peter								
			X.XX	±0.20	⑧	Add P/N and the page 3	03.11.2022	Peter	ASSMANN WSW components A company of BCS		Drawing-No. ASS 8874 CO		rev12			
			X.XXX	±0.15	⑦	Update	22.04.2022	Daniel			Customer-No.			SHEET 8 / 8		
			DIM	TOL	Id.	Modification	Date	Name								
H																
	1	2	3	4	5	6	7									