

		1		2		3		4		5		6		7			
A																A	
B																B	
C																C	
D																D	
E																E	
F																F	
G																G	
H																H	
		1		2		3		4		5		6		7			

				NOTES: 1.Housing Material: Nylon 66 UL94V-0, White; 2.Voltage Rating: 250V AC/DC; 3.Current Rating: 3A AC/DC; 4.Withstanding Voltage: 800V AC/minute; 5.Insulation Resistance: 1000MΩ Min; 6.Temperature Range: -40°C to +105°C; 7.Packing: PE bag																																																																														
				<table><tr><th rowspan="2">Poles</th><th colspan="2">Dimensions (mm)</th></tr><tr><th>A</th><th>B</th></tr><tr><td>4</td><td>2.00</td><td>5.90</td></tr><tr><td>6</td><td>4.00</td><td>7.90</td></tr><tr><td>8</td><td>6.00</td><td>9.90</td></tr><tr><td>10</td><td>8.00</td><td>11.90</td></tr><tr><td>12</td><td>10.00</td><td>13.90</td></tr><tr><td>14</td><td>12.00</td><td>15.90</td></tr><tr><td>16</td><td>14.00</td><td>17.90</td></tr><tr><td>18</td><td>16.00</td><td>19.90</td></tr><tr><td>20</td><td>18.00</td><td>21.90</td></tr><tr><td>22</td><td>20.00</td><td>23.90</td></tr><tr><td>24</td><td>22.00</td><td>25.90</td></tr><tr><td>26</td><td>24.00</td><td>27.90</td></tr><tr><td>28</td><td>26.00</td><td>29.90</td></tr><tr><td>30</td><td>28.00</td><td>31.90</td></tr><tr><td>32</td><td>30.00</td><td>33.90</td></tr><tr><td>34</td><td>32.00</td><td>35.90</td></tr><tr><td>36</td><td>34.00</td><td>37.90</td></tr><tr><td>38</td><td>36.00</td><td>39.90</td></tr><tr><td>40</td><td>38.00</td><td>41.90</td></tr><tr><td>42</td><td>40.00</td><td>43.90</td></tr><tr><td>44</td><td>42.00</td><td>45.90</td></tr><tr><td>46</td><td>44.00</td><td>47.90</td></tr><tr><td>48</td><td>46.00</td><td>49.90</td></tr><tr><td>50</td><td>48.00</td><td>51.90</td></tr></table>		Poles	Dimensions (mm)		A	B	4	2.00	5.90	6	4.00	7.90	8	6.00	9.90	10	8.00	11.90	12	10.00	13.90	14	12.00	15.90	16	14.00	17.90	18	16.00	19.90	20	18.00	21.90	22	20.00	23.90	24	22.00	25.90	26	24.00	27.90	28	26.00	29.90	30	28.00	31.90	32	30.00	33.90	34	32.00	35.90	36	34.00	37.90	38	36.00	39.90	40	38.00	41.90	42	40.00	43.90	44	42.00	45.90	46	44.00	47.90	48	46.00	49.90	50	48.00	51.90
Poles	Dimensions (mm)																																																																																	
	A	B																																																																																
4	2.00	5.90																																																																																
6	4.00	7.90																																																																																
8	6.00	9.90																																																																																
10	8.00	11.90																																																																																
12	10.00	13.90																																																																																
14	12.00	15.90																																																																																
16	14.00	17.90																																																																																
18	16.00	19.90																																																																																
20	18.00	21.90																																																																																
22	20.00	23.90																																																																																
24	22.00	25.90																																																																																
26	24.00	27.90																																																																																
28	26.00	29.90																																																																																
30	28.00	31.90																																																																																
32	30.00	33.90																																																																																
34	32.00	35.90																																																																																
36	34.00	37.90																																																																																
38	36.00	39.90																																																																																
40	38.00	41.90																																																																																
42	40.00	43.90																																																																																
44	42.00	45.90																																																																																
46	44.00	47.90																																																																																
48	46.00	49.90																																																																																
50	48.00	51.90																																																																																

RoHS compliant Unit: mm	Scale	Free						Date	Name	Description:	Wire-to-board Housing / 2.0mm / 180°
	TOLERANCE						Drawn	08.05.2021	Segal		
	X.	±0.35									
	X.X	±0.25					Approved	13.02.2025	Peter		
	X.XX	±0.20	②	Update the dimension of Housing	13.02.2025	Peter					
	X.XXX	±0.15	①	Add UL E-No. on page 1,2	15.03.2023	Peter					
	DIM	TOL	③	Drawn	08.05.2021	Segal					
	Angle	TOL	Id.	Modification	Date	Name					

ASSMANN WSW components		Drawing-No.	ASS 9009 CO	rev02
		Replace		Sheet 3/4

1 2 3 4 5 6 7

A

B

C

D

E

F

A


B

C

D

E

F



NOTES:

1. Material: Phosphor Bronze;
2. Voltage Rating: 250V AC/DC;
3. Current Rating: 3A AC/DC;
4. Withstanding Voltage: 800V AC/minute;
5. Temperature Range: -40°C to +105°C;
6. Contact Resistance: 10mΩ Max.

WSW P/N	Wire Range	Insulation OD	Finish	Qty/Reel
A-WBT-K002EG-xxCR01	AWG#22-#28	1.50mm(max)	Tin over Nickel	10,000 PCS
A-WBT-K002EG-xxCR02	AWG#22-#28	1.50mm(max)	Gold over Flash	10,000 PCS

G

H

RoHS compliant
Unit: mm

Scale	Free						Date	Name	
TOLERANCE							Drawn	08.05.2021	Segal
X.	±0.35						Approved	13.02.2025	Peter
X.X	±0.25								
X.XX	±0.20	②	Update the dimension of Housing	13.02.2025	Peter				
X.XXX	±0.15	①	Add UL E-No. on page 1,2	15.03.2023	Peter				
DIM	TOL								
		①	Drawn	08.05.2021	Segal				
Angle	TOL	Id.	Modification	Date	Name				

ASSMANN
WSW components

Description:	Wire-to-board Terminal / 2.0mm / 180°
ASSMANN WSW-No.	A-WBT-K002EG-xxCR01
Drawing-No.	ASS 9009 CO
Replace	rev02
Sheet	4/4

G

H

1 2 3 4 5 6 7