



Image for illustrative purpose only

## **Summary**

#### Request a quote

Catalog

Size

1S

Series

S - Indoor Stepped Insert

https://www.lemo.com/int\_en/solutions/originals/s-indoor-stepped-insert/bre-1s-200-nas.html


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# **Technical details**

#### Form & Material

Shell style / Model id	BRE - Cap for receptacle		
Housing material	Brass (nickel plated [SAE AMS QQ N 290]) collet and crimping tube, brass (chrome plated [SAE AMS 2460]) collet nut		
Keying	No keying		
Colour	Grey		
Weight	7.59 g		
Environment			
Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement		
Environmental sealing (IP rating)	IP61		
Temperature range	-50°C / +135°C		
Climatical Category	50/175/21		
Humidity (max)	<=95% [at 60 deg C /140 F]		
Shielding (min)	75 dB (10 MHz)		
Shielding (min)	40 dB (1 GHz)		
Shock Resistance	100 g [ 6 ms]		
Vibration	15 g [10 Hz - 2000 Hz]		
Salt Spray Corrosion	>144 hr		

## **Drawings**



No keying

### **Dimensions**

	Α	В	L	Μ	Ν	
mm.	14	11	12.5	5	85	
in.	0.55	0.43	0.49	0.2	3.35	

#### https://www.lemo.com/int\_en/solutions/originals/s-indoor-stepped-insert/bre-1s-200-nas.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.