# CFF.1S.275.PTCA12G





Image for illustrative purpose only

# **Summary**

#### Request a quote

Catalog		
Nb of contacts Coax	1	
Plug	Plug - Bridge	
Locking system	Snap-on	
Size	1S	
Suggested matching part	ERA.1S.275.CTME61	
Series	S - Indoor Stepped Insert	

# **Technical details**

### **Electrical Configuration**

and the state of t		
Nb of contacts Coax	1	
Insert configuration value	1S.275 - 1 Coax (75 Ohm)	
Insulator	T: PTFE	
Rated current	3 A	
Impedance	75 Ohm	
ОНМ	75	
VSWR	Compliant to SMPTE 2082-1 norm. See catalogue for more information.	
Vtest	1200 V (AC)	
Bucket Dia.	0.75 mm (0.03in)	
Contact Dia.	0.6 mm (0.02in)	
Form & Material		
Shell style / Model id	CFF - Bridge plug with two non-latching plugs	
Plug	Bridge	
Housing material	PA.6 (Polyamide 6) shell without treatment, other pieces nickel plated [SAE AMS QQ N 290] brass	
Locking system	Snap-on	
Keying	Circular, male	
Colour	Blue	
Weight	47.55 g	
Environment		
Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement	
Environmental sealing (IP rating)	IP50	
Endurance	1000 mating cycles	
Temperature range	-20°C / +80°C	
Climatical Category	50/175/21	
Humidity (max)	<=95% [at 60 deg C /140 F]	
Salt Spray Corrosion	>1000 hr	

### $\underline{https://www.lemo.com/int\_en/solutions/originals/s-indoor-stepped-insert/cff-1s-275-ptca12g.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.