




Insertion Loss (dB Max)		Return Loss (dB Min)		Cross Talk (dB Min)		CMR (dB Min)			OCL (uH Min)
100 KHz	1~400 MHz	1~100 MHz	100~500 MHz	1~100 MHz	100~500 MHz	1~40 MHz	40-100 MHz	100~500 MHz	@100 KHz & 0.1 mV, 8 mA
-3.0	-2.0	-22	-22+20.75Log(f/100)	-28	-19	-30	-28	-26	160



LED Color	LED Wavelength	Forward(A)	Forward(V)
Green	568nm	20mA	1.85~2.45V
Yellow	585nm	20mA	1.7~2.2V



Mating Force: 23N Max.
Durability Rating:
750 Mating Cycles Min.
Operating Temperature:
-40°C to +85°C

RoHS COMPLIANT

X.X $\pm$ 0.30
X.XX $\pm$ 0.25
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	06/28/24	New Drawing	C. Kelleher	C. Kelleher	C. Kelleher	06/28/24
A1	11/25/24	LED Pin #, Release Drawing	C. Kelleher	N/A		
						UNITS
						mm

G15LX-110S-10G-G/Y-30

No Tabs, GRN/YEL LEDs, 30u", RoHS

