GCA.1E.255.LT





Image for illustrative purpose only

Summary

Request a quote

Catalog

Size

1E

Series

E - Outdoor Stepped Insert

https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/gca-1e-255-lt.html


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

Form & Material

i onn a material			
Shell style / Model id	GCA - Earthing washer		
Housing material	Brass (CuSnZn plated)		
Keying	No keying		
Weight	0.65 g		
Environment			
Technical domain	Energy and Industrial, Test and Measurement		
Environmental sealing (IP rating)	No IP rating		
Temperature range	-55°C / +200°C		
Climatical Category	50/175/21		
Humidity (max)	<=95% [at 60 deg C /140 F]		
Shielding (min)	95 dB (10 MHz)		
Shielding (min)	80 dB (1 GHz)		
Shock Resistance	100 g [6 ms]		
Vibration	15 g [10 Hz - 2000 Hz]		

Drawings



No keying

Dimensions

	Α	В	L	Ν
mm.	20	16.2	0.5	32
in.	0.79	0.64	0.02	1.26

https://www.lemo.com/int_en/solutions/originals/e-outdoor-stepped-insert/gca-1e-255-lt.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.