

6

5

4

3

2

1

D

D

$.188 \pm .015$  [4.78 ± 0.38]  
ACROSS FLATS

.112-40 UNC-2B  
THREADS

30°

.010 [0.25] MAX.

$.160$  [4.06]  
 $.120$  [3.05]

.010 [0.25] MIN.

.030 [0.76] MIN.  
UNTHREADED

R .005 [0.13]  
MAX.

$.312 \pm .015$  [7.92 ± 0.38]


$.216$  [5.49] MIN.  
FULL THREADS

$\phi .112$  [2.83]  
 $.107$  [2.71]

.112-40 UNC-2A  
THREADS

.015 [0.38] X .015 [0.38] MAX.


THREAD LOCK SOCKET




3X FLAT WASHER



HEX NUT



SPRING LOCKWASHER



C

C

B



B

A

A

# NOTES:

1. THE REQUIREMENTS FOR THE PRODUCT HERE IN SHALL CONSIST OF MIL-DTL-24308.
2. IN THE EVENT OF A CONFLICT BETWEEN THIS DOCUMENT AND MIL-DTL-24308, MIL-DTL-24308 SHALL TAKE PRECEDENCE.

BY AP		CHK ND	3RD ANGLE 	<p>POSITRONIC BELIEVES THE DATA ON THE DRAWING TO BE RELIABLE. THE USER EMPLOYS SUCH INFORMATION AT HIS OWN DISCRETION AND RISK.</p> <p>POSITRONIC ASSUMES NO RESPONSIBILITY FOR RESULTS OBTAINED OR DAMAGES INCURRED FROM USE OF SUCH INFORMATION IN WHOLE OR IN PART.</p>  <p><b>Positronic®</b> CONNECTPOSITRONIC.COM</p>	
APR AB		RELEASED DATE: 2023-07-05	SCALE NTS		
TOLERANCES			PART NUMBER M24308/26-1Z		SERIES M24308
DIMENSIONS ARE IN INCHES. (MILLIMETER EQUIVELANTS GIVEN FOR REFERENCE ONLY)			TITLE M24308/26-1Z		
CREATED ON: 2023-07-04		SHEET SHEET 1 OF 1	REV A		

6

5

4

3

2

1