

DIN-Power shell housing C



Image is for illustration purposes only. Please refer to product description.

Part number	09 05 048 0501
Specification	DIN-Power shell housing C
HARTING eCatalogue	https://harting.com/09050480501

Identification

Category	Accessories
Identification	Type E har-bus® 64
Series of hoods/housings	DIN 41612
Type of accessory	Shell housing
Description of the accessory	20 mm

Version

Version	Top/side entry
Number of cable entries	4
Cable entry	4x
Strain relief	With cable tie
Locking type	Locking levers or locking screws
2 parts	Yes
Separable	Yes

Technical characteristics

Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP20
Isolation group	IIIa (175 ≤ CTI < 400)

Material properties

Colour (hood/housing)	RAL 7032 (pebble grey)
-----------------------	------------------------



Pushing Performance
Since 1945

Material properties

Material (accessories)	Thermoplastic Fibre-glass reinforced
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

Specifications and approvals

Railway classification	F1/I2 acc. to NFF 16-101/102
------------------------	------------------------------

Commercial data

Packaging size	10
Net weight	45.53 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140008793
ETIM	EC002943
eCl@ss	27440292 Connector component (accessories)