



Pushing Performance
Since 1945

Han-Fast Lock 4-6mm², Ag



Part number	09 08 000 7923
Specification	Han-Fast Lock 4-6mm², Ag

Identification

Category	Contacts
Series	Han-Fast® Lock
Type of contact	PCB contact
Description of the contact	Without pin

Version

Pack contents	Single contact
---------------	----------------

Technical characteristics

Conductor cross-section	4 ... 6 mm²
Rated current	≤60 A
Contact resistance	≤2 mΩ
Stripping length	7.5 mm

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (locking)	Copper alloy
Surface (locking)	Passivated
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained



Pushing Performance
Since 1945

Material properties

REACH SVHC substances	Not contained
California Proposition 65 substances	Yes

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
	CSA-C22.2 No. 182.3 ECBT8.E235076

Commercial data

Packaging size	1
Net weight	1.22 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140014893
ETIM	EC002637
eCl@ss	27460201 PCB connector (board connector)