




Pushing Performance
Since 1945

Han 1A-3+PE-s-f latch



| | |
|--------------------|---|
| Part number | 09 10 003 2700 |
| Specification | Han 1A-3+PE-s-f latch |
| HARTING eCatalogue | https://b2b.harting.com/09100032700 |

Identification

| | |
|----------|---------------------|
| Category | Inserts |
| Series | Han [®] 1A |

Version

| | |
|--------------------|--|
| Termination method | Screw termination |
| Gender | Female |
| Size | 1 A |
| Number of contacts | 3 |
| PE contact | Yes |
| Locking type | Snap-in latches |
| Details | Order separately the single wire seal or the hoods/housings for an IP65 performance. |

Details

A Han[®] 1A configuration that only consists of inserts (with or without strain relief, 09 10 000 5300) is an unenclosed connector. In this case protection against electric shock must be provided by the installation methods of the user.
Contact inserts must not be coupled or decoupled under electrical load.
Contact inserts must not be powered-up in the un-mated condition.
Contact inserts with screw termination technology (2+PE and 3+PE) only differ in the number of contacts. If both variants are used in one application, the user must prevent incorrect mating! Safety instructions according to VDE 0100-410, Chapter 414.4.3 and EN 60204-1, Chapter 13.4.5 d) must be observed.

Technical characteristics

| | |
|-----------------------------------|------------------------------|
| Conductor cross-section | 0.75 ... 1.5 mm ² |
| Rated current | 10 A |
| Rated voltage conductor-earth | 230 V |
| Rated voltage conductor-conductor | 400 V |



Pushing Performance
Since 1945

Technical characteristics

| | |
|--|----------------|
| Rated impulse voltage | 4 kV |
| Pollution degree | 3 |
| Insulation resistance | $>10^8 \Omega$ |
| Tightening torque | 0.25 Nm |
| Limiting temperature | -30 ... +90 °C |
| Mating cycles | ≥ 100 |
| Degree of protection acc. to IEC 60529 | IP20 |

Material properties

| | |
|---|--|
| Material (insert) | Polyamide (PA) |
| Colour (insert) | RAL 9005 (jet black) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Silver plated |
| Material (seal) | NBR |
| Colour (seal) | Black |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead |
| ECHA SCIP number | 5dbb3851-b94e-4e88-97a1-571845975242 |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |



Pushing Performance
Since 1945

Specifications and approvals

| | |
|----------------|--|
| Specifications | EN 45545-2 Fire protection on railway vehicles |
| | IEC 61373 Category 1 Class B |
| | IEC 60664-1 |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 15 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| ETIM | EC000438 |
| eCl@ss | 27440205 Contact insert for industrial connectors |