



Pushing Performance  
Since 1945

# Han Q Hybrid Male Data Element



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 000 9925
Specification	Han Q Hybrid Male Data Element
HARTING eCatalogue	<a href="https://b2b.harting.com/09120009925">https://b2b.harting.com/09120009925</a>

## Identification

Category	Inserts
Series	Han <sup>®</sup> Q
Description of the contact	Hybrid for M12 crimp contacts

## Version

Termination method	Crimp termination
Gender	Male
Number of contacts	4
further contacts	+ shielding
Details	Please order crimp contacts separately. 4x M12 for data element

## Technical characteristics

Conductor cross-section	0.13 ... 0.33 mm <sup>2</sup> Data
Conductor cross-section [AWG]	AWG 26 ... AWG 22 Data
Rated current (data)	2 A
Rated voltage (data)	32 V
Rated impulse voltage (data)	0.8 kV
Pollution degree (data)	3
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Limiting temperature	-40 ... +85 °C
Mating cycles	≥500



**Pushing Performance**  
Since 1945

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (shielding)	Copper alloy, nickel plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

## Commercial data

Packaging size	5
Net weight	2.4 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140282759
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors