

# Han USB module, male for patch cord




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 001 4601
Specification	Han USB module, male for patch cord
HARTING eCatalogue	<a href="https://harting.com/09140014601">https://harting.com/09140014601</a>

## Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® USB module
Size of the module	Single module
Description of the module	for patch cable

## Version

Gender	Male
Details	USB 2.0

## Technical characteristics

Rated current	1 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Rated voltage acc. to UL	30 V
Insulation resistance	$>10^{10} \Omega$
Limiting temperature	-40 ... +85 °C
Mating cycles	≥500

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)



**Pushing Performance**  
Since 1945

## Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 60352-4
UL / CSA	UL 1977 ECBT2.E235076
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	10 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140019409
ETIM	EC002312
eCI@ss	27440207 Adapter for industrial connectors (module/contact insert)