



Pushing Performance
Since 1945

Han C module, crimp-M (two part) 400pcs.



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 14 003 3003 XL |
| Specification | Han C module, crimp-M (two part) 400pcs. |
| HARTING eCatalogue | https://b2b.harting.com/09140033003XL |

Identification

| | |
|---------------------------|------------------------------|
| Category | Modules |
| Series | Han-Modular® |
| Type of module | Han® C module |
| Size of the module | Single module |
| Description of the module | for increased tensile stress |

Version

| | |
|--------------------|---|
| Termination method | Crimp termination |
| Gender | Male |
| Number of contacts | 3 |
| Details | Please order crimp contacts separately. |

Technical characteristics

| | |
|--------------------------|--|
| Conductor cross-section | 1.5 ... 10 mm² |
| Wire outer diameter | ≤4.8 mm |
| | 4.8 ... 6 mm Stripping length 18 mm |
| | 6 ... 7.5 mm Stripping length 18 mm and restricted contact removal |
| Rated current | 40 A |
| Rated voltage | 500 V |
| Rated impulse voltage | 6 kV |
| Pollution degree | 3 |
| Rated current acc. to UL | 40 A |
| Rated voltage acc. to UL | 600 V |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------------------|--|
| Insulation resistance | $>10^{10} \Omega$ |
| Stripping length | 9.5 mm 18 mm Wire outer diameter > 4.8 mm |
| Limiting temperature | -40 ... +125 °C |
| Mating cycles | $\geq 10,000$ |
| Note on the mating cycles | Mating cycles with other HMC components |

Material properties

| | |
|---|------------------------------|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Not contained |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| | |
|----------------|--------------------------|
| Specifications | IEC 60664-1 IEC 61984 |
| UL / CSA | UL 1977 ECBT2.E235076 |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|---------------|
| Packaging size | 400 |
| Net weight | 13 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140184626 |
| ETIM | EC000438 |



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440217 Module for industrial connectors (power/signals)