



Pushing Performance
Since 1945

Han® EE Push-In module, female 0,5-2,5mm



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 008 5101
Specification	Han® EE Push-In module, female 0,5-2,5mm
HARTING eCatalogue	https://b2b.harting.com/09140085101

Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® EE module
Size of the module	Single module

Version

Termination method	Push-In
Gender	Female
Number of contacts	8

Technical characteristics

Conductor cross-section	0.5 ... 2.5 mm²
Wire outer diameter	≤4.8 mm
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate (PC)
-------------------	--------------------



Pushing Performance
Since 1945

Material properties

Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984
	IEC 61373 Category 2
	IEC 60352-7

Commercial data

Packaging size	2
Net weight	7 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140408760
ETIM	EC000438
eCl@ss	27440217 Module for industrial connectors (power/signals)