

## Han shielded module basic, female




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 027 3121
Specification	Han shielded module basic, female
HARTING eCatalogue	<a href="https://b2b.harting.com/09140273121">https://b2b.harting.com/09140273121</a>

### Identification

Category	Modules
Series	Han-Modular®
Type of module	Han® Shielded module basic
Size of the module	Single module
Description of the module	With 180° shielding element

### Version

Termination method	Crimp termination
Gender	Female
Number of contacts	27
further contacts	+ shielding
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.09 ... 0.52 mm <sup>2</sup>
Wire outer diameter	≤2.3 mm
Rated current	4 A
Rated voltage	32 V
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 ... +125 °C



Pushing Performance  
Since 1945

## Technical characteristics

Mating cycles	≥500
---------------	------

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

## Commercial data

Packaging size	2
Net weight	11.9 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140185005
ETIM	EC000438
eCl@ss	27440218 Module for industrial connectors (data)