


# Han Domino DD cube, crimp (F.2)



/	
Part number	09 14 906 2101
Specification	Han Domino DD cube, crimp (F.2)
HARTING eCatalo	gue https://harting.com/09149062101

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Modules
Series	Han-Modular <sup>®</sup>
Type of module	Han <sup>®</sup> Domino DD Cube
Size of the module	Domino module
Description of the module	Large Tab
Version	
Termination method	Crimp termination
Gender	Female
Number of contacts	6
Details	Please order crimp contacts separately.

## Technical characteristics

Conductor cross-section	0.14 2.5 mm²
Wire outer diameter	≤3.9 mm
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 +125 °C
Mating cycles	≥10,000

Page 1 / 2 | Creation date 2025-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## **Technical characteristics**

Note on the mating cycles	Mating cycles with other HMC components
Material properties	
Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)
Specifications and approvals	
Specifications	IEC 60664-1 IEC 61984

#### Commercial data

UL/CSA

Packaging size	2
Net weight	5.48 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140185166
ETIM	EC000438
eCl@ss	27440217 Module for industrial connectors (power/signals)

UL 1977 ECBT2.E235076

CSA-C22.2 No. 182.3 ECBT8.E235076

Page 2 / 2 | Creation date 2025-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com