

R 15-STI-C-0,14 QMM (AU)



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 15 000 6124 |
| Specification | R 15-STI-C-0,14 QMM (AU) |
| HARTING eCatalogue | https://harting.com/09150006124 |

Identification

| | |
|-----------------|--------------------|
| Category | Contacts |
| Series | Han D [®] |
| Type of contact | Crimp contact |

Version

| | |
|-----------------------|-------------------|
| Termination method | Crimp termination |
| Gender | Male |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|-------------------------------|-------------------------------|
| Conductor cross-section | 0.14 ... 0.37 mm ² |
| Conductor cross-section [AWG] | AWG 26 ... AWG 22 |
| Rated current | ≤10 A |
| Contact resistance | ≤3 mΩ |
| Stripping length | 8 mm |

Material properties

| | |
|---------------------|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Gold plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|--------------------------------------|
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |

Specifications and approvals

| | |
|----------------|--------------------------|
| Specifications | IEC 60664-1 IEC 61984 |
|----------------|--------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 100 |
| Net weight | 0.4 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140021907 |
| ETIM | EC000796 |
| eCl@ss | 27440204 Contact for industrial connectors |