



Pushing Performance  
Since 1945

# DIN-Signal 2C/2R shroud press-in 5.90




Image is for illustration purposes only. Please refer to product description.

Part number	09 23 000 9957
Specification	DIN-Signal 2C/2R shroud press-in 5.90
HARTING eCatalogue	<a href="https://b2b.harting.com/09230009957">https://b2b.harting.com/09230009957</a>

## Identification

Category	Accessories
Series	DIN 41612
Type of accessory	Pin shroud
Description of the accessory	for female connectors type 2C for male connectors type 2R

## Version

Termination length	13 mm
	16.2 mm
	17 mm
Fixing	Press-in fixing

## Technical characteristics

Isolation group	IIIa ( $175 \leq CTI < 400$ )
PCB thickness	2.6 mm $\pm 0.5$
	5.8 mm $\pm 0.5$
	6.6 mm $\pm 0.5$

## Material properties

Material (accessories)	Thermoplastic
Colour (accessories)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e



**Pushing Performance**  
Since 1945

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Specifications and approvals

Railway classification	F1/I2 acc. to NFF 16-101/102
------------------------	------------------------------

## Commercial data

Packaging size	100
Net weight	0.01 g
Country of origin	Vietnam
European customs tariff number	85389099
GTIN	5713140041271
ETIM	EC002943
eCl@ss	27440292 Connector component (accessories)