




## Han 24B-HSE-DL-NPTF 3/4 Zoll



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 30 524 0530                                                                        |
| Specification      | Han 24B-HSE-DL-NPTF 3/4 Zoll                                                          |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09305240530">https://b2b.harting.com/09305240530</a> |

### Identification

|                          |                    |
|--------------------------|--------------------|
| Category                 | Hoods/Housings     |
| Series of hoods/housings | Han <sup>®</sup> B |
| Type of hood/housing     | Hood               |
| Type                     | High construction  |

### Version

|                      |                                                   |
|----------------------|---------------------------------------------------|
| Locking type         | Double locking lever                              |
| Size                 | 24 B                                              |
| Version              | Side entry                                        |
| Cable entry          | 1x NPTF 3/4"                                      |
| Field of application | Standard hoods/housings for industrial connectors |

### Technical characteristics

|                                        |                      |
|----------------------------------------|----------------------|
| Limiting temperature                   | -40 ... +125 °C      |
| Degree of protection acc. to IEC 60529 | IP65<br>IP66<br>IP67 |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |
| RoHS                    | compliant            |
| ELV status              | compliant            |
| China RoHS              | e                    |



Pushing Performance

## Material properties

|                             |                                                           |
|-----------------------------|-----------------------------------------------------------|
| REACH Annex XVII substances | No                                                        |
| REACH ANNEX XIV substances  | No                                                        |
| REACH SVHC substances       | Yes                                                       |
| REACH SVHC substances       | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |

## Specifications and approvals

|           |                                   |
|-----------|-----------------------------------|
| Approvals | DNV GL                            |
| UL / CSA  | UL 1977 ECBT2.E235076             |
|           | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                               |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 319 g                                    |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |