

## Han C M crimp contact 4 mm<sup>2</sup> Ag-SMC



Image is for illustration purposes only. Please refer to product description.

Part number	09 32 000 6107 XL
Specification	Han C M crimp contact 4 mm <sup>2</sup> Ag-SMC
HARTING eCatalogue	<a href="https://b2b.harting.com/09320006107XL">https://b2b.harting.com/09320006107XL</a>

### Identification

Category	Contacts
Series	Han <sup>®</sup> C
Type of contact	Crimp contact

### Version

Gender	Male
Manufacturing process	Turned contacts

### Technical characteristics

Conductor cross-section	4 mm <sup>2</sup>
Conductor cross-section [AWG]	AWG 12
Rated current	≤40 A
Contact resistance	≤1 mΩ
Stripping length	9.5 mm
Mating cycles	≥500

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50



**Pushing Performance**  
Since 1945

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984

## Commercial data

Packaging size	1,000
Net weight	2 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140187863
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors