

## Han C-Contact Female with pin



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 32 000 6295                                                                |
| Specification      | Han C-Contact Female with pin                                                 |
| HARTING eCatalogue | <a href="https://harting.com/09320006295">https://harting.com/09320006295</a> |

### Identification

|                 |                    |
|-----------------|--------------------|
| Category        | Contacts           |
| Series          | Han <sup>®</sup> C |
| Type of contact | PCB contact        |

### Version

|                       |                   |
|-----------------------|-------------------|
| Termination method    | Crimp termination |
| Gender                | Male              |
| Manufacturing process | Turned contacts   |

### Technical characteristics

|                    |       |
|--------------------|-------|
| Rated current      | ≤40 A |
| Contact resistance | ≤3 mΩ |

### Material properties

|                             |                                                        |
|-----------------------------|--------------------------------------------------------|
| Material (contacts)         | Copper alloy                                           |
| Surface (contacts)          | Silver plated                                          |
| RoHS                        | compliant with exemption                               |
| RoHS exemptions             | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                  | compliant with exemption                               |
| China RoHS                  | 50                                                     |
| REACH Annex XVII substances | Not contained                                          |
| REACH ANNEX XIV substances  | Not contained                                          |
| REACH SVHC substances       | Yes                                                    |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| REACH SVHC substances                | Lead                                 |
| ECHA SCIP number                     | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes                                  |
| California Proposition 65 substances | Lead<br>Nickel                       |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
|----------------|--------------------------|

## Commercial data

|                                |                                            |
|--------------------------------|--------------------------------------------|
| Packaging size                 | 25                                         |
| Net weight                     | 1.9 g                                      |
| Country of origin              | Germany                                    |
| European customs tariff number | 85366990                                   |
| GTIN                           | 5713140049116                              |
| ETIM                           | EC000796                                   |
| eCl@ss                         | 27440204 Contact for industrial connectors |