



Pushing Performance  
Since 1945

# Han E AV 10 Pos. M Insert Term Block Rig




Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 33 010 4635                                                                |
| Specification      | Han E AV 10 Pos. M Insert Term Block Rig                                      |
| HARTING eCatalogue | <a href="https://harting.com/09330104635">https://harting.com/09330104635</a> |

## Identification

|               |                                          |
|---------------|------------------------------------------|
| Category      | Inserts                                  |
| Series        | Han E <sup>®</sup> AV                    |
| Element       | Terminal block connector                 |
| Specification | Right hand version<br>Multi contour (MK) |

## Version

|                    |                   |
|--------------------|-------------------|
| Termination method | Screw termination |
| Gender             | Male              |
| Size               | 10 B              |
| Number of contacts | 10                |
| PE contact         | Yes               |

## Technical characteristics

|                          |                             |
|--------------------------|-----------------------------|
| Conductor cross-section  | 0.2 ... 2.5 mm <sup>2</sup> |
| Rated current            | 16 A                        |
| Rated voltage            | 500 V                       |
| Rated impulse voltage    | 6 kV                        |
| Pollution degree         | 3                           |
| Rated voltage acc. to UL | 600 V                       |
| Insulation resistance    | >10 <sup>10</sup> Ω         |
| Contact resistance       | ≤4 mΩ                       |
| Tightening torque        | 0.5 Nm                      |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                      |                 |
|----------------------|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Mating cycles        | ≥500            |

## Material properties

|                                           |                                                        |
|-------------------------------------------|--------------------------------------------------------|
| Material (insert)                         | Polycarbonate (PC)                                     |
| Colour (insert)                           | RAL 7032 (pebble grey)                                 |
| Material (contacts)                       | Copper alloy                                           |
| Surface (contacts)                        | Silver plated                                          |
| Material flammability class acc. to UL 94 | V-0                                                    |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50                                                     |
| REACH Annex XVII substances               | Not contained                                          |
| REACH ANNEX XIV substances                | Not contained                                          |
| REACH SVHC substances                     | Yes                                                    |
| REACH SVHC substances                     | Lead                                                   |
| California Proposition 65 substances      | Yes                                                    |
| California Proposition 65 substances      | Lead<br>Nickel                                         |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

## Specifications and approvals

|                |                          |
|----------------|--------------------------|
| Specifications | IEC 60664-1<br>IEC 61984 |
| UL / CSA       | UL 1977 ECBT2.E235076    |
| Approvals      | DNV GL                   |

## Commercial data

|                                |          |
|--------------------------------|----------|
| Packaging size                 | 1        |
| Net weight                     | 113.02 g |
| Country of origin              | Romania  |
| European customs tariff number | 85366990 |



**Pushing Performance**  
Since 1945

## Commercial data

|        |                                                   |
|--------|---------------------------------------------------|
| GTIN   | 5713140051188                                     |
| ETIM   | EC000438                                          |
| eCl@ss | 27440205 Contact insert for industrial connectors |