

# Han High Temp 10E-c Male



Part number	09 33 810 2604
Specification	Han High Temp 10E-c Male
HARTING eCatalogue	https://b2b.harting.com/09338102604

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Inserts
Series	Han E <sup>®</sup> High Temp

#### Version

Termination method	Crimp termination
Gender	Male
Size	10 B
Number of contacts	10
PE contact	Yes
Details	Please order crimp contacts separately.

#### Technical characteristics

Conductor cross-section	0.5 2.5 mm²
Conductor cross-section [AWG]	AWG 20 AWG 14
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 +200 °C With Han® High Temp components
Mating cycles	≥500



# Material properties

Material (insert)	Liquid crystal polymer (LCP)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)
	· · · ·

# Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076
	UL 2237 PVVA2.E318390
	CSA-C22.2 No. 182.3 PVVA8.E318390

### Commercial data

Packaging size	1
Net weight	54.5 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140185852
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors