

Han PushPull PFT metal circular HIFF



| Part number | 09 35 012 0312 |
|--------------------|--------------------------------------|
| Specification | Han PushPull PFT metal circular HIFF |
| HARTING eCatalogue | https://harting.com/09350120312 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|-----------------------------|---------------------------------|
| Series | Han [®] PushPull (V14) |
| Type of hood/housing | Bulkhead mounted housing |
| Description of hood/housing | for circular panel cut out |

Version

| Locking type PushPull |
|-----------------------|
|-----------------------|

Technical characteristics

| Limiting temperature | -40 +70 °C |
|--|------------|
| Mating cycles | ≥500 |
| Degree of protection acc. to IEC 60529 | IP65 |
| | IP67 |

Material properties

| Material (hood/housing) | Zinc die-cast |
|---|--|
| Surface (hood/housing) | Nickel plated |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |



Material properties

| REACH ANNEX XIV substances | Not contained |
|--------------------------------------|----------------|
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

| Specifications | IEC 61076-3-117 EN 45545-2 |
|----------------|-------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079 |
| PROFINET | Yes |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 49 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140053922 |
| ETIM | EC000437 |
| eCl@ss | 27440202 Shell for industrial connectors |