

## Han PP Power PFT M25 crimp



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 231 0332
Specification	Han PP Power PFT M25 crimp
HARTING eCatalogue	<a href="https://harting.com/09352310332">https://harting.com/09352310332</a>

### Identification

Category	Connectors
Series	Han® PushPull (V14)
Identification	Power
Element	Panel feed trough set
Specification	Circular panel cut out
Features	Intuitive locking mechanism

### Version

Termination method	Crimp termination
Shielding	Unshielded
Number of contacts	5
Locking type	PushPull
Pack contents	incl. bulkhead mounted housing and male insert Without contacts

### Technical characteristics

Conductor cross-section	0.25 ... 2.5 mm²
Conductor cross-section [AWG]	AWG 22 ... AWG 12
Rated current	16 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated voltage acc. to UL	600 V



**Pushing Performance**  
Since 1945

## Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	Grey
Surface (contacts)	Silver plated
Material (hood/housing)	Polycarbonate (PC)
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

## Specifications and approvals

Specifications	IEC 61076-3-118 EN 45545-2
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	17.74 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140054172
eCl@ss	27440114 Rectangular connector (for field assembly)
ETIM	EC002636
UNSPSC 24.0	39121408



**Pushing Performance**  
Since 1945

Mating face

