

Han 16 HPR Cover Toggle Locking



| Part number | 09 40 016 5401 |
|--------------------|---------------------------------|
| Specification | Han 16 HPR Cover Toggle Locking |
| HARTING eCatalogue | https://harting.com/09400165401 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Accessories |
|------------------------------|--|
| Series of hoods/housings | Han [®] HPR |
| Type of accessory | Protection cover |
| Description of the accessory | for bulkhead mounted housings for surface mounted housings |

Version

| Size | 16 B |
|--------------|----------------|
| Locking type | Toggle locking |

Technical characteristics

| Limiting temperature | -40 +125 °C |
|--|---------------|
| Degree of protection acc. to IEC 60529 | IP65 IP68 |
| Type rating acc. to UL 50 / UL 50E | 4 4X 12 |

Material properties

| Material (hood/housing) | Aluminium die-cast Corrosion resistant |
|-------------------------|--|
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (locking) | Stainless steel |
| RoHS | compliant |



Material properties

| ELV status | compliant |
|--------------------------------------|----------------------------|
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R1 (HL 1-3) R7 (HL 1-3) |

Specifications and approvals

| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
|-----------|--|
| Approvals | DNV GL |

Commercial data

| Packaging size | 1 |
|--------------------------------|--|
| Net weight | 33.18 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140057784 |
| ETIM | EC002314 |
| eCl@ss | 27440208 Cap for industrial connectors |