

Han 3HPR Hood Top Entry PG 13.5 Toggle I



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 40 703 0402 |
| Specification | Han 3HPR Hood Top Entry PG 13.5 Toggle I |
| HARTING eCatalogue | https://harting.com/09407030402 |

Identification

| | |
|--------------------------|----------------------|
| Category | Hoods / Housings |
| Series of hoods/housings | Han [®] HPR |
| Type of hood/housing | Hood |

Version

| | |
|-------------------------|---|
| Size | 3 A |
| Version | Top entry |
| Number of cable entries | 1 |
| Cable entry | 1x Pg 13.5 |
| Locking type | Toggle locking |
| Field of application | Hoods/housings for harsh outdoor environments |
| Details | By using the inserts of Han [®] Q and Han A [®] series, the sealing on the insert has to be removed. The sealing screw of the insert must be replaced by the sealing screw of the hood/housing. |
| Pack contents | With seal screw |

Technical characteristics

| | |
|--|--|
| Tightening torque | 0.5 Nm M3 insert fixing screw |
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP65 IP68 |



Pushing Performance
Since 1945

Technical characteristics

| | |
|------------------------------------|----|
| Type rating acc. to UL 50 / UL 50E | 4 |
| | 4X |
| | 12 |

Material properties

| | |
|--------------------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (locking) | Stainless steel |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |
| | Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R1 (HL 1-3) |
| | R7 (HL 1-3) |

Specifications and approvals

| | |
|-----------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | CE |
| | DNV GL |

Commercial data

| | |
|--------------------------------|---------------|
| Packaging size | 1 |
| Net weight | 74.8 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140058521 |
| ETIM | EC000437 |



Pushing Performance
Since 1945

Commercial data

eCl@ss

27440202 Shell for industrial connectors