




**Pushing Performance**  
Since 1945

# Han3A RJ45 Cat5 PFT 8p angled



|               |                               |
|---------------|-------------------------------|
| Part number   | 09 45 215 1101                |
| Specification | Han3A RJ45 Cat5 PFT 8p angled |

## Identification

|               |                               |
|---------------|-------------------------------|
| Category      | Connectors                    |
| Series        | RJ45                          |
| Element       | Panel feed through            |
| Specification | Straight, inner vertical jack |

## Version

|                    |  |
|--------------------|--|
| Size               | 3 A                                    |
| Shielding          | Fully shielded, 360° shielding contact |
| Number of contacts | 8                                      |
| Fixing             | Screwable in cover plates              |

## Technical characteristics

|  |                              |
|--|------------------------------|
| Transmission characteristics           | Cat. 5 Class D up to 100 MHz |
| Data rate                              | 10 Mbit/s                    |
|  | 100 Mbit/s                   |
|  | 1 Gbit/s                     |
|  | 2.5 Gbit/s                   |
| Limiting temperature                   | -40 ... +70 °C               |
| Mating cycles                          | ≥500                         |
| Degree of protection acc. to IEC 60529 | IP65                         |
|  | IP67                         |

## Material properties

|                         |               |
|-------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| Surface (hood/housing)  | Powder-coated |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |   |
|--------------------------------------|---|
| Colour (hood/housing)                | Grey  |
| RoHS                                 | compliant with exemption  |
| RoHS exemptions                      | 6(a) / 6(a)-I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight |
| ELV status                           | compliant with exemption  |
| China RoHS                           | 50  |
| REACH Annex XVII substances          | Not contained   |
| REACH ANNEX XIV substances           | Not contained   |
| REACH SVHC substances                | Yes   |
| REACH SVHC substances                | Lead  |
| California Proposition 65 substances | Yes   |
| California Proposition 65 substances | Lead<br>Nickel<br>Naphthalene   |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| PROFINET  | Yes    |

## Commercial data

|                                |                                       |
|--------------------------------|---------------------------------------|
| Packaging size                 | 1                                     |
| Net weight                     | 55 g                                  |
| Country of origin              | Romania                               |
| European customs tariff number | 85366990                              |
| GTIN                           | 5713140059566                         |
| ETIM                           | EC002636                              |
| eCl@ss                         | 27440113 Rectangular connectors (set) |