

HPP V4 USB 2.0 A, C-PFT



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 45 245 1902 |
| Specification | HPP V4 USB 2.0 A, C-PFT |
| HARTING eCatalogue | https://b2b.harting.com/09452451902 |

Identification

| | |
|-----------------------------|-----------------------|
| Category | Connectors |
| Series | HARTING PushPull (V4) |
| Identification | USB |
| Element | Panel feed through |
| Specification | USB 2.0 type A |
| Description of hood/housing | Compact |

Version

| | |
|--------------------|--|
| Shielding | Fully shielded, 360° shielding contact |
| Number of contacts | 4 |

Technical characteristics

| | |
|--|----------------|
| Limiting temperature | -40 ... +70 °C |
| Mating cycles | ≥750 |
| Degree of protection acc. to IEC 60529 | IP65 IP67 |

Material properties

| | |
|-----------------------------|---------------|
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|-------------------|
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Antimony trioxide |
| | Lead |
| | Nickel |
| | Naphthalene |

Specifications and approvals

| | |
|----------------|--------------------------------|
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
| | EN 45545-2 |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 13.33 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140059894 |
| ETIM | EC002636 |
| eCl@ss | 27440114 Rectangular connector (for field assembly) |