

## Han EMC 15 Base Panel



Image is for illustration purposes only. Please refer to product description.

Part number	09 62 015 0301
Specification	Han EMC 15 Base Panel
HARTING eCatalogue	<a href="https://b2b.harting.com/09620150301">https://b2b.harting.com/09620150301</a>

### Identification

Category	Hoods / Housings
Series of hoods/housings	Han <sup>®</sup> EMC
Type of hood/housing	Bulkhead mounted housing

### Version

Size	10 A
Locking type	Single locking lever
Han-Easy Lock <sup>®</sup>	Yes
Field of application	Hoods/Housings for higher EMC requirements

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
Material (locking)	Polycarbonate (PC) Stainless steel
Colour (locking)	RAL 7037 (dust grey)



**Pushing Performance**  
Since 1945

## Material properties

Material flammability class acc. to UL 94  
(locking levers)

V-0

RoHS

compliant

ELV status

compliant

China RoHS

e

REACH Annex XVII substances

Not contained

REACH ANNEX XIV substances

Not contained

REACH SVHC substances

Yes

REACH SVHC substances

Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate

ECHA SCIP number

60b1a572-bb3f-476f-9307-b7d1688bd90c

California Proposition 65 substances

Yes

California Proposition 65 substances

Nickel

Fire protection on railway vehicles

EN 45545-2 (2020-08)

Requirement set with Hazard Levels

R22 (HL 1-3)

R23 (HL 1-3)

## Specifications and approvals

UL / CSA

UL 1977 ECBT2.E235076

CSA-C22.2 No. 182.3 ECBT8.E235076

Approvals

CE

DNV GL

## Commercial data

Packaging size

1

Net weight

60 g

Country of origin

Germany

European customs tariff number

85389099

GTIN

5713140073364

ETIM

EC000437

eCl@ss

27440202 Shell for industrial connectors