

## Han 24EMC/B-HBM-Rear Fit-DL-w/o frame



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 62 824 0392                                                                        |
| Specification      | Han 24EMC/B-HBM-Rear Fit-DL-w/o frame                                                 |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09628240392">https://b2b.harting.com/09628240392</a> |

### Identification

|                             |                                |
|-----------------------------|--------------------------------|
| Category                    | Hoods / Housings               |
| Series of hoods/housings    | Han <sup>®</sup> EMC/B         |
| Type of hood/housing        | Bulkhead mounted housing       |
| Description of hood/housing | External seal<br>Rear mounting |
| Type                        | Low construction               |

### Version

|                            |                                            |
|----------------------------|--------------------------------------------|
| Size                       | 24 B                                       |
| Locking type               | Double locking lever                       |
| Han-Easy Lock <sup>®</sup> | Yes                                        |
| Field of application       | Hoods/Housings for higher EMC requirements |

### Technical characteristics

|                                        |                                                |
|----------------------------------------|------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                |
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Mating cycles                          | ≥500                                           |
| Degree of protection acc. to IEC 60529 | IP66                                           |
| Type rating acc. to UL 50 / UL 50E     | 4<br>12                                        |

### Material properties

|                         |                    |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
| Surface (hood/housing)  | Uncoated           |



**Pushing Performance**  
Since 1945

## Material properties

|                                                            |                      |
|------------------------------------------------------------|----------------------|
| Colour (hood/housing)                                      | Unpainted            |
| Material (seal)                                            | NBR                  |
| Material (locking)                                         | Polycarbonate (PC)   |
|                                                            | Stainless steel      |
| Colour (locking)                                           | RAL 7037 (dust grey) |
| Material (accessories)                                     | Polyamide (PA)       |
|                                                            | Stainless steel      |
| Material flammability class acc. to UL 94 (locking levers) | V-0                  |

## Specifications and approvals

|           |                                   |
|-----------|-----------------------------------|
| UL / CSA  | UL 1977 ECBT2.E235076             |
|           | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals | CE                                |
|           | DNV GL                            |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140172074                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |