

## Han 24HPR VarioShell-2x24HPR-Set1



Image is for illustration purposes only. Please refer to product description.

Part number	10 40 124 1001
Specification	Han 24HPR VarioShell-2x24HPR-Set1
HARTING eCatalogue	<a href="https://b2b.harting.com/10401241001">https://b2b.harting.com/10401241001</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> HPR VarioShell
Type of hood/housing	Complete set
Description of hood/housing	Angled

### Version

Size	24 HPR
Cable entry	for 2x 24 HPR
Field of application	Hoods/housings for harsh outdoor environments
Details	Please note the installation manual.
Pack contents	Bulkhead mounted housing Mounting cover 2x Bulkhead mounted housing 24 HPR enlarged Fixing screws

### Technical characteristics

Tightening torque	4 Nm Mounting cover 12 Nm Fixing screws 12 Nm PE screw 10 Nm Bulkhead mounted housing 24 HPR enlarged
Limiting temperature	-40 ... +125 °C
Degree of protection acc. to IEC 60529	IP66 IP67 IP68 IP69



Pushing Performance

## Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material (locking)	Stainless steel

## Specifications and approvals

CE	Yes
----	-----

## Commercial data

Packaging size	1
Net weight	3.66 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors