

Han HPR HPTC 850 CS UNSH IP65/67 150



Part number	10 40 281 2137
Specification	Han HPR HPTC 850 CS UNSH IP65/67 150
HARTING eCatalogue	https://harting.com/10402812137

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Connector sets
Series of hoods/housings	Han [®] HPR HPTC
Type of hood/housing	Complete set
Description of hood/housing	Cable side With integrated cable gland
Type of cable	Copper cable (round)
Features	for stranded wires according to IEC 60228 Class 5

Version

Size	3
Shielding	360° shielding
Coding	16 coding options
Number of cable entries	1
Cable entry	1x M40
Field of application	Hoods/housings for harsh outdoor environments

Technical characteristics

Conductor cross-section	150 mm²
Rated current	850 A
Rated voltage	3,600 V
Rated impulse voltage	20 kV
Pollution degree	4
Overvoltage category	III



Technical characteristics

Limiting temperature	-40 +125 °C
Mating cycles	≥25
Degree of protection acc. to IEC 60529	IP68 IP69
Clamping range	16 20.5 mm

Material properties

Material (insert)	Polyamide (PA)
Material (hood/housing)	Aluminium die-cast Corrosion resistant
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH ANNEX XIV substances REACH SVHC substances	Not contained Yes
REACH SVHC substances	Yes
REACH SVHC substances REACH SVHC substances	Yes Lead

Specifications and approvals

	EN 50467
	EN 50124-1
Specifications	IEC 61373 Category 1 Class B
	EN 45545
	EN 60137

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85359000
GTIN	5713140189935
eCl@ss	27440113 Rectangular connectors (set)

Product data sheet 10 40 281 2137 Han HPR HPTC 850 CS UNSH IP65/67 150



	+~
Commercial da	10

ETIM EC002636